

* FREEFIX 6470-W-2

Date revised: 06.03.2016

6956470

Version: 9 / GB

Master No. M-401

Print date: 20.04.16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

FREEFIX 6470-W-2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Purpose of use: Raw substance formulas for manufacturing shaped parts from unsaturated polyester / vinyl ester resins.

1.3. Details of the supplier of the safety data sheet

Address

BÜFA Composite Systems
GmbH & Co. KG
Hohe Looge 2-8
26180 Rastede

Telephone no. +49 4402 975-0

Fax no. +49 4402 975-400

Information provided Department product safety / +49 4402 975-415
by / telephone

E-Mail produktsicherheit-compositesystems@buefa.de

1.4. Emergency telephone number

Giftzentrale Goettingen: +49 551 19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3 H226

Skin Irrit. 2 H315

Eye Irrit. 2 H319

Repr. 2 H361d

STOT RE 1 H372 Organs: Ear; Route of exposure: inhalative

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008

For explanation of abbreviations see section 16.

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Hazard pictograms



Signal word

Danger

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure:

Ear; Route of exposure: inhalative

* FREEFIX 6470-W-2

Date revised: 06.03.2016

6956470

Version: 9 / GB

Master No. M-401

Print date: 20.04.16

Precautionary statements

P201	Obtain special instructions before use.
P210.9	Keep away from sparks, open flames and other ignition sources. No smoking.
P260.8	Do not breathe vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains Styrene

2.3. Other hazards

The product does not contain PBT/vPvB-substances.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous ingredients****Styrene**

CAS No.	100-42-5
EINECS no.	202-851-5
Registration no.	01-2119457861-32-XXXX
Concentration	>= 10 < 20 %

Flam. Liq. 3	H226	
Skin Irrit. 2	H315	
Acute Tox. 4	H332	
Eye Irrit. 2	H319	
STOT SE 3	H335	
STOT RE 1	H372	Organs: Ear; Route of exposure: inhalative
Asp. Tox. 1	H304	
Repr. 2	H361d	
Aquatic Chronic 3	H412	

1,4-Dihydroxybenzene

CAS No.	123-31-9
EINECS no.	204-617-8
Registration no.	01-2119524016-51-XXXX
Concentration	>= 0,01 < 0,1 %

Aquatic Acute 1	H400
Skin Sens. 1	H317
Eye Dam. 1	H318
Carc. 2	H351
Acute Tox. 4	H302
Muta. 2	H341

Aquatic Acute 1 H400 M = 10

Complete text of hazard statements in chapter 16

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Adhere to personal protective measures when giving first aid. Remove soiled or soaked clothing immediately, do not allow to dry.

* FREEFIX 6470-W-2

Date revised: 06.03.2016

6956470

Version: 9 / GB

Master No. M-401

Print date: 20.04.16

After inhalation

Remove the casualty into fresh air and keep him calm. Irregular breathing/no breathing: artificial respiration. In the event of symptoms take medical treatment.

After skin contact

Wash off immediately with soap and water.

After eye contact

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Seek medical advice immediately. Remove contact lenses

After ingestion

Rinse mouth thoroughly with water. Summon a doctor immediately. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. If individual is drowsy or unconscious place in recovery position (on left side, with head down).

4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur: Headache, Dizziness, Nausea

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Alcohol-resistant foam, Dry powder, Carbon dioxide

Non suitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of combustion evolution of dangerous gases possible. In the event of fire the following can be released: Carbon monoxide (CO); Nitrogen oxides (NO_x); dense black smoke

5.3. Advice for firefighters

Use self-contained breathing apparatus.

Collect contaminated fire-fighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin, eyes and clothing. Use personal protective clothing. Keep away sources of ignition. Ensure adequate ventilation. Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not discharge into the subsoil/soil. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Pick up with absorbent material (eg sand, kieselgur, acid binder, universal binder, sawdust). When picked up, treat material as prescribed under Section 13 "Disposal".

6.4. Reference to other sections

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Provide good ventilation of working area (local exhaust ventilation if necessary). Observe the usual precautions for handling chemicals.

* FREEFIX 6470-W-2

Date revised: 06.03.2016

6956470

Version: 9 / GB

Master No. M-401

Print date: 20.04.16

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Vapours can form an explosive mixture with air.

7.2. Conditions for safe storage, including any incompatibilities

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

7.3. Specific end use(s)

No information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limit values

Styrene

List	EH40			
Type	WEL			
Value	430	mg/m ³	100	ppm(V)
Short term exposure limit	1080	mg/m ³	250	ppm(V)
Maximum limit value; Skin resorption / sensibilisation: Pregnancy group: Status: 2011				

Derived No/Minimal Effect Levels (DNEL/DMEL)

Styrene

Reference substance	Styrene			
DNEL				
Conditions	Worker	Acute	inhalative	Systemic effects
Concentration	289		mg/m ³	
DNEL				
Conditions	Worker	Long term	inhalative	Systemic effects
Concentration	85		mg/m ³	
DNEL				
Conditions	Worker	Acute	inhalative	Local effects
Concentration	306		mg/m ³	
DNEL				
Conditions	Worker	Long term	dermal	Systemic effects
Concentration	406		mg/kg/d	

8.2. Exposure controls

Appropriate engineering controls

Use only in well ventilated areas.

Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

General protective and hygiene measures

Provide good ventilation of working area (local exhaust ventilation if necessary). Avoid contact with skin and eyes. Do not inhale gases/vapours/aerosols.

Respiratory protection

If workplace limits are exceeded, a respiratory protection approved for this particular job must be worn.

Short term: filter apparatus, Filter A

Hand protection

Chemical resistant gloves

Appropriate Material	Butyl rubber		
Material thickness	0,7	mm	
Breakthrough time	= 30	min	

* FREEFIX 6470-W-2

Date revised: 06.03.2016

6956470

Version: 9 / GB

Master No. M-401

Print date: 20.04.16

Eye protection

Tightly fitting safety glasses

Body protection

Clothing as usual in the chemical industry.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Form	Pasty		
Colour	Various, depending on coloration		
Odour	of styrene		
Flash point			
Value	32		°C
Efflux time			
Value	> 61		s
Method	DIN EN ISO 2431 - 6 mm		
Density			
Value	1,65		g/cm ³
Temperature	20	°C	

9.2. Other information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reactions when stored and handled according to prescribed instructions.

10.2. Chemical stability

The product is stable.

10.3. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4. Conditions to avoid

Protect from heat and direct sunlight.

10.5. Incompatible materials

Reactions with peroxides and other radical components.

10.6. Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute oral toxicity**

Based on available data, the classification criteria are not met.

Acute dermal toxicity

Based on available data, the classification criteria are not met.

Acute inhalational toxicity

ATE	74,68	mg/l
Administration/Form	Vapors	
Method	calculated value (Regulation (EC) No. 1272/2008)	
ATE	9,49	mg/l
Administration/Form	Dust/Mist	
Method	calculated value (Regulation (EC) No. 1272/2008)	

* FREEFIX 6470-W-2

Date revised: 06.03.2016

6956470

Version: 9 / GB

Master No. M-401

Print date: 20.04.16

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

evaluation irritant

The classification criteria are met

Serious eye damage/irritation

evaluation irritant

The classification criteria are met

Sensitization

Based on available data, the classification criteria are not met.

Sensitization (Components)**Styrene**

evaluation non-sensitizing

Mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

evaluation Suspected of damaging the unborn child.

The classification criteria are met

Specific Target Organ Toxicity (STOT)**Single exposure**

Based on available data, the classification criteria are not met.

Repeated exposure

The classification criteria are met

evaluation Causes damage to organs through prolonged or repeated exposure

Aspiration hazard

Based on available data, the classification criteria are not met.

Other information

Inhalation of the vapours causes irritation of the respiratory tract and mucous membrane, headaches, nausea, giddiners, vomiting.

SECTION 12: Ecological information**12.1. Toxicity****Fish toxicity****Styrene**

LC/EC/IC50 > 1,0 to 10 mg/l

Daphnia toxicity**Styrene**

Species Daphnia magna
LC/EC/IC50 > 1,0 to 10 mg/l

Algae toxicity**Styrene**

LC/EC/IC50 > 1,0 to 10 mg/l

Bacteria toxicity

No toxicological data are available.

12.2. Persistence and degradability

For this subsection there is no ecotoxicological data available on the product as such.

Biodegradability**Styrene**

evaluation Readily biodegradable (according to OECD criteria)

* FREEFIX 6470-W-2

Date revised: 06.03.2016

6956470

Version: 9 / GB

Master No. M-401

Print date: 20.04.16

12.3. Bioaccumulative potential

For this subsection there is no ecotoxicological data available on the product as such.

12.4. Mobility in soil

For this subsection there is no ecotoxicological data available on the product as such.

12.5. Results of PBT and vPvB assessment

The product does not contain PBT/vPvB-substances.

12.6. Other adverse effects

For this subsection there is no ecotoxicological data available on the product as such.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations for the product**

EWC waste code 07 02 08* other still bottoms and reaction residues
 The listed waste code numbers, according to the European Waste Catalogue (EWC), are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company.

Disposal recommendations for packaging

Packaging that cannot be cleaned should be disposed off as product waste.

SECTION 14: Transport information**Land transport ADR/RID****14.1. UN number**

UN number 1866

14.2. UN proper shipping name

RESIN SOLUTION

14.3. Transport hazard class(es)

Class 3

14.4. Packing group

Packing group III
 Special provision 640E
 Remarks Viscous product: Transport according to paragraph 2.2.3.1.5 ADR/RID
 Tunnel restriction code D/E

Marine transport IMDG/GGVSee**14.1. UN number**

UN number 1866

14.2. UN proper shipping name

RESIN SOLUTION

14.3. Transport hazard class(es)

Class 3

14.4. Packing group

Packing group III
 Remarks Transport according to 2.3.2.5 of the IMDG Code
 EmS F-E, S-E

SECTION 15: Regulatory information *****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC**

VOC (EU) 0,78 %

Major-accident categories acc. 2012/18/EU ***

Category P5c FLAMMABLE LIQUID

* FREEFIX 6470-W-2

Date revised: 06.03.2016

6956470

Version: 9 / GB

Master No. M-401

Print date: 20.04.16

Other information

The product does not contain substances of very high concern (SVHC).

15.2. Chemical safety assessment

No information available

SECTION 16: Other information**Hazard statements listed in Chapter 3**

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure:
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Abbreviations

CAS: Chemical Abstracts Service
 EAK: Europäischer Abfallkatalog
 EINECS: European Inventory of Existing Commercial Chemical Substances
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: Very persistent and very bioaccumulative
 VOC: Volatile Organic Compound

CLP categories listed in Chapter 3

Acute Tox. 4	Acute toxicity, Category 4
Aquatic Acute 1	Hazardous to the aquatic environment, acute, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage, Category 1
Eye Irrit. 2	Eye irritation, Category 2
Flam. Liq. 3	Flammable liquid, Category 3
Muta. 2	Germ cell mutagenicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin irritation, Category 2
Skin Sens. 1	Skin sensitization, Category 1
STOT RE 1	Specific target organ toxicity - repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: ***
 This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.