

SAERTEX Product Index:	7002632-08014016-630
SAERTEX Article Description:	U-E-1042g/m ² -630mm
SAERTEX SAP-Number // Supplier reference:	30002864 // 8E15003100 (input: OCV / 3B SE1500) 30006101 // 8E15003101 (input: NEG 2002/2001)

Product Properties	Unit	0°	90°	Stitching
Construction (EN13473)		Ply 2	Ply 1	
Nominal area weight	g/m ²	945	80	17,0
Tolerance of layer areal weight		± 5%	± 5%	± 3g/m ²
Nominal linear weight	tex	2400	300	11,0
Material Type		E-Glass	E-Glass	PES
<i>It is not allowed to mix the raw material input per ply and per product.</i>		NEG 2002 17µm	NEG 2001 14µm	-
		OCV/3B SE1500 17µm	OCV/3B SE1500 16µm	-
Stitch type		-	-	Tricot
Gauge		-	-	10
Stitch length	mm	-	-	3,75

Total areal weight (nominal)	1042g/m ² ± 54g/m ² (988 - 1096g/m ² equal to ± 5,2% tolerance)
Length of fringes	≤ 10mm
Width tolerance (0° to 0°)	630mm: ± 5mm
Roll length	90m (-1m / +5m)
Minimum roll length	48m