



# West & Senior Limited

Milltown Street • Radcliffe • Manchester • M26 1WE • United Kingdom

Tel +44 (0) 161 724 7131 • Fax +44 (0) 161 724 9519

<http://www.westsenior.co.uk> • [info@westsenior.co.uk](mailto:info@westsenior.co.uk)

## SAFETY DATA SHEET SIGNAL RED RAL3001 EPOXY PIGMENT

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name SIGNAL RED RAL3001 EPOXY PIGMENT

Product number WS27207C

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses COLOURING OF EPOXIDE COMPOUNDS & SYSTEMS

#### 1.3. Details of the supplier of the safety data sheet

Supplier WEST AND SENIOR LIMITED.  
MILLTOWN STREET  
RADCLIFFE  
MANCHESTER. M26 1WE.  
TEL + 44 01617247131  
FAX + 44 01617249519  
[info@westsenior.co.uk](mailto:info@westsenior.co.uk)

#### 1.4. Emergency telephone number

Emergency telephone 24 HOUR EMERGENCY TELEPHONE NUMBER : +44 7379825059

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (SI 2019 No. 720)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 2 - H411

Human health See Section 11 for additional information on health hazards.

Environmental The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

#### 2.2. Label elements

##### Hazard pictograms



Signal word Warning

Hazard statements  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H411 Toxic to aquatic life with long lasting effects.

## SIGNAL RED RAL3001 EPOXY PIGMENT

<b>Precautionary statements</b>	<p>P261 Avoid breathing vapour/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P391 Collect spillage.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
<b>Supplemental label information</b>	EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
<b>Contains</b>	bis-[4-(2,3-epoxipropoxy)phenyl]propane, Formaldehyde, polymer with (chloromethyl)oxirane and phenol, mw <=700, oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>bis-[4-(2,3-epoxipropoxy)phenyl]propane</b> CAS number: 1675-54-3                      EC number: 216-823-5	<b>30-60%</b>
<b>Classification</b> Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411	
<b>Formaldehyde, polymer with (chloromethyl)oxirane and phenol, mw &lt;=700</b> CAS number: 9003-36-5                      EC number: 500-006-8	<b>10-30%</b>
<b>Classification</b> Skin Irrit. 2 - H315 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411	
<b>oxirane, mono[(C12-14-alkyloxy)methyl] derivs.</b> CAS number: 68609-97-2	<b>5-10%</b>
<b>Classification</b> Skin Irrit. 2 - H315 Skin Sens. 1 - H317	

## SIGNAL RED RAL3001 EPOXY PIGMENT

<b>TITANIUM DIOXIDE</b>	<b>1-5%</b>
CAS number: 13463-67-7	EC number: 236-675-5
<b>Classification</b> Not Classified	

The full text for all hazard statements is displayed in Section 16.

**Composition comments** This mixture contains  $\geq 1\%$  Titanium Dioxide (CAS 13463-67-7) The Annex VI classification of Titanium Dioxide does not apply to this mixture according to its Note 10.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>Inhalation</b>	Move affected person to fresh air at once. If breathing stops, provide artificial respiration. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep affected person warm and at rest. Get medical attention immediately.
<b>Ingestion</b>	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Give milk instead of water if readily available. Get medical attention immediately.
<b>Skin contact</b>	Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention. Get medical attention promptly if symptoms occur after washing.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>Inhalation</b>	Vapours may irritate throat/respiratory system.
<b>Ingestion</b>	There may be soreness and redness of the mouth and throat.
<b>Skin contact</b>	Prolonged contact may cause redness, irritation and dry skin.
<b>Eye contact</b>	Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

#### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	No specific recommendations. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.
<b>Specific treatments</b>	Provide eyewash station.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Use fire-extinguishing media suitable for the surrounding fire.
<b>Unsuitable extinguishing media</b>	Not known.

#### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards</b>	Fire or high temperatures create: Toxic gases/vapours/fumes of: Carbon dioxide (CO <sub>2</sub> ). Carbon monoxide (CO). Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.
-------------------------	---

## SIGNAL RED RAL3001 EPOXY PIGMENT

**Hazardous combustion products** Carbon dioxide (CO<sub>2</sub>). Carbon monoxide (CO). Halogenated hydrocarbons.

### 5.3. Advice for firefighters

**Protective actions during firefighting** Isolate area. Very toxic to aquatic life. Control run-off water by containing and keeping it out of sewers and watercourses.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Use air-supplied respirator, gloves and protective goggles.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** For personal protection, see Section 8. Keep unnecessary and unprotected personnel from entering the area. Avoid inhalation of vapours. Isolate area.

### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses. For waste disposal, see Section 13.

### 6.4. Reference to other sections

**Reference to other sections** Wear protective clothing as described in Section 8 of this safety data sheet. See Section 11 for additional information on health hazards. Collect and dispose of spillage as indicated in Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Do not eat, drink or smoke when using this product. Persons susceptible to allergic reactions should not handle this product.  
Avoid contact with skin and eyes. Avoid inhalation of vapours and spray/mists.  
Store in tightly-closed, original container. Wear suitable protective clothing as protection against splashing or contamination.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in tightly-closed, original container in a dry, cool and well-ventilated place.

**Storage class** Chemical storage.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure controls/Personal protection

### 8.1. Control parameters

#### Occupational exposure limits

#### TITANIUM DIOXIDE

EH40 WEL, Time Weighted Average (TWA):, Inhalable dust. 10 mg/m<sup>3</sup>, 8 h

EH40 WEL, Time Weighted Average (TWA):, Respirable dust. 4 mg/m<sup>3</sup>, 8 h

## SIGNAL RED RAL3001 EPOXY PIGMENT

### bis-[4-(2,3-epoxipropoxy)phenyl]propane (CAS: 1675-54-3)

<b>DNEL</b>	Workers - Dermal; Short term systemic effects: 8.3 mg/kg, bw/day
	Workers - Inhalation; Short term systemic effects: 12.3 mg/m <sup>3</sup>
	Workers - Dermal; Long term systemic effects: 8.3 mg/kg, bw/day
	Workers - Inhalation; Long term systemic effects: 12.3 mg/m <sup>3</sup>
	General population - Dermal; Short term systemic effects: 3.6 mg/kg, bw/day
	General population - Inhalation; Short term systemic effects: 0.75 mg/m <sup>3</sup>
	General population - Oral; Short term systemic effects: 0.75 mg/kg, bw/day
	General population - Dermal; Long term systemic effects: 3.6 mg/kg, bw/day
	General population - Inhalation; Long term systemic effects: 0.75 mg/m <sup>3</sup>
<b>PNEC</b>	Fresh water; 3 µg/l
	marine water; 0.3 µg/l
	STP; 10 mg/l
	Sediment (Freshwater); 0.5 mg/kg
	Sediment (Marinewater); 0.5 mg/kg
	Sediment; 0.05 mg/kg
Intermittent release; 0.013 mg/l	

### Formaldehyde, polymer with (chloromethyl)oxirane and phenol, mw <=700 (CAS: 9003-36-5)

<b>DNEL</b>	Industry - Dermal; Short term local effects: 8.3 ppm
	Industry - Dermal; Long term systemic effects: 104.15 mg/kg/day
	Industry - Inhalation; Long term systemic effects: 29.39 mg/m <sup>3</sup>
	Consumer - Dermal; Long term systemic effects: 62.5 mg/kg/day
	Consumer - Inhalation; Long term systemic effects: 8.7 mg/m <sup>3</sup>
	Consumer - Oral; Long term systemic effects: 6.25 mg/kg/day
<b>PNEC</b>	- Fresh water; 0.003 mg/l
	- marine water; 0.0003 mg/l
	- Sediment (Freshwater); 0.294 mg/kg
	- Sediment (Marinewater); 0.0294 mg/kg
	- Soil; 0.237 mg/kg
	- Intermittent release; 0.0254

### C.I. PIGMENT RED 254 (CAS: 84632-65-5)

<b>DNEL</b>	Workers - Inhalation; Long term local effects: 1.25 mg/m <sup>3</sup>
	Consumer - Inhalation; Long term local effects: 10 mg/m <sup>3</sup>
<b>PNEC</b>	Fresh water; 0.499 mg/l
	Intermittent release; 0.499 mg/l
	marine water; 0.499 mg/l
	STP; 1 mg/l
	Sediment (Marinewater); 668 mg/l
	Sediment (Freshwater); 668 mg/l
Soil; 1 mg/l	

### oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (CAS: 68609-97-2)

## SIGNAL RED RAL3001 EPOXY PIGMENT

**DNEL** Workers - Inhalation; Long term systemic effects: 3.6 mg/m<sup>3</sup>  
 Workers - Dermal; Long term systemic effects: 1 mg/kg/day  
 General population - Inhalation; Long term systemic effects: 0.87 mg/m<sup>3</sup>  
 General population - Dermal; Long term systemic effects: 0.5 mg/kg/day  
 General population - Oral; Long term systemic effects: 0.5 mg/kg/day

**PNEC** Fresh water; 0.106 mg/l  
 Fresh water, Intermittent release; 0.072 mg/l  
 marine water; 0.011 mg/l  
 STP; 10 mg/l  
 Sediment (Freshwater), dw; 307.16 mg/kg  
 Sediment (Marinewater), dw; 30.72 mg/kg  
 Soil, dw; 1.234 mg/kg

### TITANIUM DIOXIDE (CAS: 13463-67-7)

**DNEL** Workers - Inhalation; Long term local effects: 10 mg/m<sup>3</sup>  
 Professional - Inhalation; Long term local effects: 10 mg/m<sup>3</sup>  
 Consumer - Oral; Long term systemic effects: 700 mg/kg/day

**PNEC** marine water; 0.0184 mg/l  
 Fresh water; 0.184 mg/l  
 Intermittent release; 0.193 mg/l  
 STP; 100 mg/l  
 Sediment, marine water; 100 mg/kg  
 Sediment, Fresh water; 1000 mg/kg  
 Soil; 100 mg/kg

### C.I. PIGMENT YELLOW 83 (CAS: 5567-15-7)

**DNEL** Workers - Dermal; Long term systemic effects: 45 mg/kg/day  
 Workers - Inhalation; Long term local effects: 3 mg/m<sup>3</sup>  
 General population - Dermal; Long term systemic effects: 28 mg/kg/day  
 General population - Oral; Long term systemic effects: 28 mg/kg/day

### Trimethylolpropane (CAS: 77-99-6)

**DNEL** Workers - Inhalation; Long term systemic effects: 3.3 mg/m<sup>3</sup>  
 Workers - Dermal; Long term systemic effects: 0.94 mg/kg  
 Consumer - Inhalation; Long term systemic effects: 0.58 mg/m<sup>3</sup>  
 Consumer - Dermal; Long term systemic effects: 0.34 mg/kg  
 Consumer - Oral; Long term systemic effects: 0.34 mg/kg

## 8.2. Exposure controls

### Protective equipment



### Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

### Eye/face protection

Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Chemical splash goggles.

## SIGNAL RED RAL3001 EPOXY PIGMENT

<b>Hand protection</b>	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.
<b>Other skin and body protection</b>	Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
<b>Hygiene measures</b>	Provide eyewash station. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.
<b>Respiratory protection</b>	If ventilation is inadequate, suitable respiratory protection must be worn. Check that the respirator fits tightly and the filter is changed regularly.
<b>Environmental exposure controls</b>	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Liquid. or Coloured paste.
<b>Colour</b>	Various colours.
<b>Odour</b>	Slight.
<b>Odour threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point</b>	Not determined.
<b>Initial boiling point and range</b>	Not determined.
<b>Flash point</b>	150°C
<b>Evaporation rate</b>	Not determined.
<b>Evaporation factor</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	Not determined.
<b>Other flammability</b>	Not available.
<b>Vapour pressure</b>	Not determined.
<b>Vapour density</b>	Not determined.
<b>Relative density</b>	Not available.
<b>Bulk density</b>	Not available.
<b>Solubility(ies)</b>	Not available.
<b>Partition coefficient</b>	Not available.
<b>Auto-ignition temperature</b>	(ASTM D 1929) 400°C
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	Not determined.
<b>Explosive properties</b>	Not applicable.

## SIGNAL RED RAL3001 EPOXY PIGMENT

<b>Explosive under the influence of a flame</b>	No
<b>Oxidising properties</b>	Not available.
<b>Comments</b>	Information given is applicable to the product as supplied.

### 9.2. Other information

<b>Other information</b>	No information required.
--------------------------	--------------------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

<b>Reactivity</b>	Stable at normal ambient temperatures and when used as recommended.
-------------------	---

### 10.2. Chemical stability

<b>Stability</b>	No particular stability concerns.
------------------	-----------------------------------

### 10.3. Possibility of hazardous reactions

<b>Possibility of hazardous reactions</b>	Hazardous reactions or instability may occur under certain conditions of storage or use.
---	--

### 10.4. Conditions to avoid

<b>Conditions to avoid</b>	Avoid releasing into the environment.
----------------------------	---------------------------------------

### 10.5. Incompatible materials

<b>Materials to avoid</b>	No data recorded.
---------------------------	-------------------

### 10.6. Hazardous decomposition products

<b>Hazardous decomposition products</b>	Does not decompose when used and stored as recommended. This product contains a diaryl pigment. This product should not be used if the processing temperature exceeds 200°C because of possible thermal decomposition, which can, with prolonged exposure or further increased temperature, form e.g. traces of aromatic amines. 3,3'-Dichloro-benzidine.
---	---

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Toxicological information on ingredients.

#### bis-[4-(2,3-epoxypropoxy)phenyl]propane

##### Acute toxicity - oral

<b>Notes (oral LD<sub>50</sub>)</b>	LD <sub>50</sub> 11400 mg/kg, Oral, Rat
-------------------------------------	---

##### Acute toxicity - dermal

<b>Notes (dermal LD<sub>50</sub>)</b>	LD <sub>50</sub> >2000 mg/kg, Dermal, Rabbit
---------------------------------------	--

##### Acute toxicity - inhalation

<b>Notes (inhalation LC<sub>50</sub>)</b>	Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at ambient temperature.
---	--

##### Skin corrosion/irritation

<b>Skin corrosion/irritation</b>	Irritating to skin.
----------------------------------	---------------------

##### Serious eye damage/irritation

<b>Serious eye damage/irritation</b>	Causes eye irritation.
--------------------------------------	------------------------



## SIGNAL RED RAL3001 EPOXY PIGMENT

### Respiratory sensitisation

**Respiratory sensitisation** May cause sensitisation or allergic reactions in sensitive individuals.

### Skin sensitisation

**Skin sensitisation** May cause an allergic skin reaction.

### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

**Genotoxicity - in vivo** Based on available data the classification criteria are not met.

### Carcinogenicity

**IARC carcinogenicity** IARC Group 3 Not classifiable as to its carcinogenicity to humans.

### Reproductive toxicity

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Based on available data the classification criteria are not met.

### Aspiration hazard

**Aspiration hazard** Based on available data the classification criteria are not met.

### Formaldehyde, polymer with (chloromethyl)oxirane and phenol, mw <=700

#### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** LD<sub>50</sub> >2000 mg/kg, Oral, Rat

#### Acute toxicity - inhalation

**Notes (inhalation LC<sub>50</sub>)** Not applicable.

#### Specific target organ toxicity - single exposure

**STOT - single exposure** Not available.

#### oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

#### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 17,100.0

**Species** Rat

**ATE oral (mg/kg)** 17,100.0

#### Acute toxicity - dermal

**Notes (dermal LD<sub>50</sub>)** Not applicable.

#### Acute toxicity - inhalation

**Notes (inhalation LC<sub>50</sub>)** Not applicable.

#### Skin corrosion/irritation

**Animal data** Moderately irritating.

#### Serious eye damage/irritation

## SIGNAL RED RAL3001 EPOXY PIGMENT

**Serious eye damage/irritation** Causes serious eye irritation.

**Skin sensitisation**

**Skin sensitisation** Severe skin irritation.

### SECTION 12: Ecological information

**Ecotoxicity** Dangerous for the environment. May cause long-term adverse effects in the aquatic environment.

**Ecological information on ingredients.**

**bis-[4-(2,3-epoxipropoxy)phenyl]propane**

**Ecotoxicity** Toxic to aquatic life.

**12.1. Toxicity**

**Ecological information on ingredients.**

**bis-[4-(2,3-epoxipropoxy)phenyl]propane**

**Toxicity** WGK 2

**Acute aquatic toxicity**

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: 1.3 mg/l, Fish

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 2.1 mg/l, Ceriodaphnia dubia (water flea)

**Acute toxicity - aquatic plants** EC<sub>50</sub>, 72 hours: 11 mg/l, Algae

**Formaldehyde, polymer with (chloromethyl)oxirane and phenol, mw <=700**

**Acute aquatic toxicity**

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: 2.54 mg/l, Fish

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 2.55 mg/l, Daphnia magna

**Acute toxicity - aquatic plants** EC<sub>50</sub>, 72 hours: >1000 mg/l, Algae

**oxirane, mono[(C12-14-alkyloxy)methyl] derivs.**

**Acute aquatic toxicity**

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: > 1.8 mg/l, Oncorhynchus mykiss (Rainbow trout)

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 7.2 mg/l, Daphnia magna

**Acute toxicity - aquatic plants** EC<sub>50</sub>, 72 hours: ~ 844 mg/l, Freshwater algae

**12.2. Persistence and degradability**

**Persistence and degradability** There are no data on the degradability of this product.

**Ecological information on ingredients.**

## SIGNAL RED RAL3001 EPOXY PIGMENT

### bis-[4-(2,3-epoxipropoxy)phenyl]propane

**Biodegradation** Not readily biodegradable.

### Formaldehyde, polymer with (chloromethyl)oxirane and phenol, mw <=700

**Persistence and degradability** Not readily biodegradable.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** Not available.

#### Ecological information on ingredients.

### bis-[4-(2,3-epoxipropoxy)phenyl]propane

**Bioaccumulative potential** log Pow: 2.65 - 3.78, BCF: 3 - 31 31.00,

### Formaldehyde, polymer with (chloromethyl)oxirane and phenol, mw <=700

**Bioaccumulative potential** log Pow: 3.3, BCF: 150 150.00,

#### 12.4. Mobility in soil

**Mobility** No data available.

#### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current UK criteria.

#### 12.6. Other adverse effects

**Other adverse effects** Not known.

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

**General information** Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Avoid the spillage or runoff entering drains, sewers or watercourses.

**Waste class** EWC NUMBER : Allocation of a waste code number in accordance with the European Waste Catalogue, should be carried out in agreement with an EA authorised waste disposal company.

### **SECTION 14: Transport information**

**Road transport notes** SP375 – These substances when carried in Single or Combination packaging's containing a net Qty per single or inner packaging of 5ltr or less for liquids or having a net mass per single or inner packaging of 5kg or less for solids, are not subject to any provisions of ADR provided the packaging's meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8

## SIGNAL RED RAL3001 EPOXY PIGMENT

### Sea transport notes

Chapter 2.10 – 2.10.2.7 – Marine Pollutants packaged in Single or Combination packaging's containing a net Qty per single or inner packaging of 5ltr or less for liquids or having a net mass per single or inner packaging of 5kg or less for solids, are not subject to any other provisions of this code relevant to Marine Pollutants, provided the packaging's meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of Marine Pollutants also meeting the Criteria for inclusion in another class, all provisions of this code relevant to any additional hazards continue to apply

### Air transport notes

A197 - These substances when carried in Single or Combination packaging's containing a net Qty per single or inner packaging of 5ltr or less for liquids or having a net mass per single or inner packaging of 5kg or less for solids, are not subject to any other provisions of these regulations provided the packaging's meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8

### 14.1. UN number

UN No. (ADR/RID)	3082
UN No. (IMDG)	3082
UN No. (ICAO)	3082
UN No. (ADN)	3082


### 14.2. UN proper shipping name

Proper shipping name (ADR/RID)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Bisphenol F Mixture)
Proper shipping name (IMDG)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Bisphenol F Mixture)
Proper shipping name (ICAO)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Bisphenol F Mixture)
Proper shipping name (ADN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Bisphenol F Mixture)

### 14.3. Transport hazard class(es)

ADR/RID class	9
ADR/RID classification code	M6
ADR/RID label	9
IMDG class	9
ICAO class/division	9
ADN class	9

### Transport labels



### 14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ADN packing group	III

## SIGNAL RED RAL3001 EPOXY PIGMENT

ICAO packing group III

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



### 14.6. Special precautions for user

EmS F-A, S-F

ADR transport category 3

Emergency Action Code •3Z

Hazard Identification Number 90  
(ADR/RID)

Tunnel restriction code (E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**National regulations** Control of Substances Hazardous to Health Regulations 2002 (as amended).

**EU legislation** Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

**Guidance** A guide to local exhaust ventilation (LEV) HSG258 (as amended)  
Workplace Exposure Limits EH40.

### 15.2. Chemical safety assessment

Not applicable.

## SECTION 16: Other information

Revision date 26/01/2023

Revision 1

SDS number 43284

## SIGNAL RED RAL3001 EPOXY PIGMENT

### **Hazard statements in full**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

The information contained within this document is presented in good faith and is believed to be correct. West and Senior Limited makes no representation as to the accuracy and/or completeness of this information. This information is issued on the condition that the user will determine the safety and suitability of products for their purposes prior to use. All technical details and values presented are deemed typical and do not constitute a delivery specification.