



**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**SEAJET 015 UNDERWATER PRIMER**

Product code: 255VR - Version 2 - Revision Date: 10-09-2019

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Paint and/or related product.

**1.3. Details of the supplier of the safety data sheet**

Chugoku Paints B.V., Sluisweg 12, 4794 SW Heijningen, Po Box 73, 4793 ZH Fijnaart, The Netherlands, Tel.+31-167-526100, E-mail: msdsregistration@cmpeurope.eu

**1.4. Emergency telephone number**

National Poisons Information Service: England & Wales / NHS dial 111, Scotland NHS 24, <http://www.npis.org>

N.Ireland, Contact your local GP or pharmacist during normal hours,

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP].**

Flam. Liq. 3 H226	Flammable liquid and vapour.
Skin Irrit. 2 H315	Causes skin irritation.
Eye Irrit. 2 H319	Causes serious eye irritation.
Skin Sens. 1 H317	May cause an allergic skin reaction.
STOT SE 3 H335	May cause respiratory irritation.
STOT RE 2 H373	May cause damage to organs through prolonged or repeated exposure.
Aquatic Chronic 3 H412	Harmful to aquatic life with long lasting effects.

**2.2. Label elements**

**Regulation (EC) No 1272/2008.**



GHS02



GHS07



GHS08

**Signalword:**

**Warning**

**Hazard Statements:**

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements:**

**Prevention:**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapours/spray.
P280	Wear protective gloves, protective clothing, eye protection, face protection.



Product code: 255VR - Version 2 - Revision Date: 10-09-2019

Response:

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage & Disposal: -

**Contains (EC 1272/2008 18.3(b)):**

Reaction mass of Ethylbenzene and Xylene.

Isobutyl Methyl Ketone.

Bis-[4-(2,3-epoxipropoxy)phenyl]propane.

Contains epoxy constituents. See information supplied by the manufacturer. - This information is supplied in the present Safety Data Sheet.

Extended details regarding health and environment, see section 11 & 12.

**Supplemental hazard information:**

The mixture may be a skin sensitiser. It may also be a skin irritant and repeated contact may increase this effect.

**2.3. Other hazards: Not available.**

Product code: 255VR - Version 2 - Revision Date: 10-09-2019

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

Substances presenting a health or environmental hazard within the meaning of Regulation (EC) No. 1272/2008, assigned a Community workplace exposure limit, classified as PBT/vPvB or included in the Candidate List.

(\*). See Section 16 for full text.

Substance Name	Reg.nr's	Conc.range	Symbol	Hazard statement (*)	M(ac)=1	M(chr)=1
Hydrocarbons, C10, Aromatics, <1% Naphthalene.	EG-nr: 918-811-1 CAS-nr: 1189173-42-9 Index: -	15-20		H304 - Asp. Tox. 1 H336 - STOT SE 3 H411 - Aquatic Chronic 2 EUH066	-	-
Reach #: 01-2119463583-34					M(ac)=1	M(chr)=1
Reaction Mass Of Ethylbenzene And Xylene.	EG-nr: 905-588-0 CAS-nr: - Index: -	10-15		H226 - Flam. Liq. 3 H304 - Asp. Tox. 1 H312 - Acute Tox. 4 H315 - Skin Irrit. 2	H319 - Eye Irrit. 2 H332 - Acute Tox. 4 H335 - STOT SE 3 H373 - STOT RE 2	-
Reach #: 01-2119488216-32					-	-
Isobutyl Methyl Ketone.	EG-nr: 203-550-1 CAS-nr: 108-10-1 Index: 606-004-00-4	5-10		H225 - Flam. Liq. 2 H332 - Acute Tox. 4 H319 - Eye Irrit. 2 H335 - STOT SE 3	EUH066	-
Reach #: 01-2119473980-30					-	-
Aluminium Powder (Stabilised).	EG-nr: 231-072-3 CAS-nr: 7429-90-5 Index: 013-002-00-1	1-5		H228 H261	-	-
Reach #: 01-2119529243-45					-	-
Bis-[4-(2,3-Epoxypropoxy)Phenyl]Propane.	EG-nr: 216-823-5 CAS-nr: 1675-54-3 Index: 603-073-00-2	0,1-1		H319 - Eye Irrit. 2 H315 - Skin Irrit. 2 H317-(1B) - Skin Sens. 1B H411 - Aquatic Chronic 2	-	-
Reach #: 01-2119456619-26					M(ac)=1	M(chr)=1
Naphtha (Petroleum), Hydrotreated Heavy.	EG-nr: 265-150-3 CAS-nr: 64742-48-9 Index: 649-327-00-6	0,1-1		H226 - Flam. Liq. 3 H304 - Asp. Tox. 1 H336 - STOT SE 3 EUH066	-	-
Reach #: 01-2119486659-16					-	-
Methanol.	EG-nr: 200-659-6 CAS-nr: 67-56-1 Index: 603-001-00-X	0,1-0,5		H225 - Flam. Liq. 2 H331 - Acute Tox. 3 H311 - Acute Tox. 3 H301 - Acute Tox. 3	H370** - STOT SE 1	-
Reach #: 01-2119433307-44					-	-

**SECTION 4: First aid measures****4.1. Description of first aid measures**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

**Inhalation**

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

**Skin contact**

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

**Eye contact**

Remove contact lenses, if present and easy to do. Irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

**Ingestion**

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed****Potential acute symptoms and effects****Inhalation**

Exposure to vapours may cause a health hazard. Serious effects may be delayed following exposure.

May cause respiratory irritation.

**Skin contact**

Causes skin irritation.

**Eye contact**

Causes serious eye irritation.

**Ingestion**

No known significant effects or critical hazards.

**Potential delayed symptoms and effects****Inhalation**

No specific data.

**Skin contact**

Adverse symptoms may include the following: irritation, redness

**Eye contact**

Adverse symptoms may include the following: irritation, watering, redness

**Ingestion**

No specific data.

**4.3. Indication of any immediate medical attention and special treatment needed****Notes to physician**

In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**

No specific treatment.

Product code: 255VR - Version 2 - Revision Date: 10-09-2019

**SECTION 5: Firefighting measures****5.1. Extinguishing media**

Recommended: alcohol resistant foam, CO2, powders, water spray/mist

**Extinguishing media which must not be used for safety reasons:**

Water jet. Zinc dust containing products should not be extinguished with water.

**5.2. Special hazards arising from the substance or mixture**

Fire will produce dense black smoke.

Exposure to decomposition products may cause a health hazard. See Section 10.

Appropriate breathing apparatus may be required.

**5.3. Advice for firefighters**

Cool closed containers exposed to fire with water.

Do not allow run-off from fire fighting to enter drains or water courses.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Exclude sources of ignition and ventilate the area. Avoid breathing vapours.

Refer to protective measures listed in sections 7 and 8.

**6.2. Environmental precautions**

Do not allow to enter drains or watercourses.

If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

**6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).

Clean preferably with a detergent - avoid use of solvents.

**6.4. Reference to other sections**

See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded.

Electrical equipment should be protected to the appropriate standard. No sparking tools should be used.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

Operators should wear anti-static footwear and clothing and floors should be of the conducting type.

Isolate from sources of heat, sparks and open flame.

Avoid skin and eye contact.

Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture.

Avoid inhalation of dust from sanding.

Smoking, eating and drinking should be prohibited in application area.

For personal protection see Section 8.

Never use pressure to empty: container is not a pressure vessel.

Always keep in containers of same material as the original one.

Comply with the health and safety at work laws.

Do not allow to enter drains or water courses.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

Product code: 255VR - Version 2 - Revision Date: 10-09-2019

**Information on fire and explosion protection**

Vapours are heavier than air and may spread along floors.  
 Vapours may form explosive mixtures with air.

**7.2. Conditions for safe storage, including any incompatibilities**

Store in accordance with local regulations.

**Notes on joint storage**

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

**Additional information on storage conditions**

Observe label precautions.  
 Store between 0°C and 40°C in a dry, well ventilated place away from sources of heat and direct sunlight.  
 Keep container tightly closed.  
 Keep away from sources of ignition.  
 No smoking.  
 Prevent unauthorised access.  
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.

**7.3. Specific end use(s)**

Application: Airless spray, brush, roller (See also the Technical Datasheet)

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

Limits for occupational exposure and / or biological limit values		
	LIMIT VALUES TWA8h - STEL15 ppm-mg/m <sup>3</sup>	LIMIT VALUES TWA8h - STEL15 ppm-mg/m <sup>3</sup>
Hydrocarbons, C10, Aromatics, <1% Naphthalene.	TWA8h - ppm / - mg/m <sup>3</sup>	TWA8h - ppm / - mg/m <sup>3</sup>
	STEL - ppm / - mg/m <sup>3</sup>	STEL15 - ppm / - mg/m <sup>3</sup>
	Annotations -	Notation -
Reaction Mass Of Ethylbenzene And Xylene.	TWA8h - ppm / - mg/m <sup>3</sup>	TWA8h - ppm / - mg/m <sup>3</sup>
	STEL - ppm / - mg/m <sup>3</sup>	STEL15 - ppm / - mg/m <sup>3</sup>
	Annotations -	Notation -
Isobutyl Methyl Ketone.	TWA8h 50 ppm / 208 mg/m <sup>3</sup>	TWA8h 20 ppm / 83 mg/m <sup>3</sup>
	STEL 100 ppm / 416 mg/m <sup>3</sup>	STEL15 50 ppm / 208 mg/m <sup>3</sup>
	Annotations Sk	Notation -
Aluminium Powder (Stabilised).	TWA8h - ppm / 10inh,4resp. mg/m <sup>3</sup>	TWA8h - ppm / - mg/m <sup>3</sup>
	STEL - ppm / - mg/m <sup>3</sup>	STEL15 - ppm / - mg/m <sup>3</sup>
	Annotations -	Notation -
Bis-[4-(2,3-Epoxypropoxy)Phenyl]Propane.	TWA8h - ppm / - mg/m <sup>3</sup>	TWA8h - ppm / - mg/m <sup>3</sup>
	STEL - ppm / - mg/m <sup>3</sup>	STEL15 - ppm / - mg/m <sup>3</sup>
	Annotations -	Notation -
Naphtha (Petroleum), Hydrotreated Heavy.	TWA8h - ppm / - mg/m <sup>3</sup>	TWA8h 20 ppm / 116 mg/m <sup>3</sup>
	STEL - ppm / - mg/m <sup>3</sup>	STEL15 50 ppm / 290 mg/m <sup>3</sup>
	Annotations -	Notation Skin
Methanol.	TWA8h 200 ppm / 266 mg/m <sup>3</sup>	TWA8h 200 ppm / 260 mg/m <sup>3</sup>
	STEL 250 ppm / 333 mg/m <sup>3</sup>	STEL15 - ppm / - mg/m <sup>3</sup>
	Annotations Sk	Notation Skin

U.K. - TWA=Time Weighted Average (8hr) - STEL=Short-term exposure limit (15-minute reference period) - H.S.E. Health and Safety Commission.

Europe - TWA = Time Weight Average (8hr) - Measured or calculated in relation to a reference period of 8 hours time-weighted average (TWA) - STEL = Short-term exposure limit - A limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified - SCOEL

Annotations / Notations:

BMGVs: Biological monitoring guidance values.

Carc: Capable of causing cancer and/or heritable genetic damage.

Product code: 255VR - Version 2 - Revision Date: 10-09-2019

Inh.: Inhalable fraction.

Resp.: Respirable fraction.

Sen: Capable of causing occupational asthma.

Sk: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.

Skin: A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin.

**DNEL**

DNEL - Not available

**PNEC**

PNEC - Not available

**8.2. Exposure controls**

**Appropriate engineering controls**

Provide adequate ventilation.

Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

**Individual protection measures, such as personal protective equipment**

**Personal Protection**

Respiratory protection



If workers could be exposed to concentrations above the exposure limit they should use a respirator to EN 140, fitted with a filter suitable for both particulates and vapours to EN14387, with an assigned protection factor of at least 10 (e.g. A2P3)

Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes.

Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Hand protection



There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. At repeated or prolonged contact; gloves (EN374).

Viton-gloves offer good protection for intense contact with most solvents, e.g. complete immersion in solvent.

Nitrile gloves offer good protection during spray application.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

<b>Gloves for repeated or prolonged exposure (Permeation breakthrough times &gt; 480 min) - High Protection:</b>		
<b>Material:</b>	<b>Minimum Thickness:</b>	<b>Chemical resistance:</b>
Polyethylene (PE) Gloves	0,062mm	High

Product code: 255VR - Version 2 - Revision Date: 10-09-2019

<b>Gloves for repeated or prolonged exposure (Permeation breakthrough times 240 - 480 min) - High Protection:</b>		
<b>Material:</b> Polyethylene (PE) Gloves	<b>Minimum Thickness:</b> 0,062mm	<b>Chemical resistance:</b> High
<b>Gloves for repeated or prolonged exposure (Permeation breakthrough times 120-240 min) - Medium Protection:</b>		
<b>Material:</b> Polyethylene (PE) Gloves	<b>Minimum Thickness:</b> 0,062mm	<b>Chemical resistance:</b> High
<b>Gloves for repeated or prolonged exposure (Permeation breakthrough times 60 - 120 min) - Medium Protection:</b>		
<b>Material:</b> Polyethylene (PE) Gloves	<b>Minimum Thickness:</b> 0,062mm	<b>Chemical resistance:</b> High
<b>Gloves for short term exposure / splash protection (Permeation breakthrough times 30 - 60 min):</b>		
<b>Material:</b> Polyethylene (PE) Gloves	<b>Minimum Thickness:</b> 0,062mm	<b>Chemical resistance:</b> High
Nitrile Gloves	0,425mm	High
<b>Gloves for short term exposure / splash protection (Permeation breakthrough times 10 - 30 min):</b>		
<b>Material:</b> Polyethylene (PE) Gloves	<b>Minimum Thickness:</b> 0,062mm	<b>Chemical resistance:</b> High
Butyl Viton Gloves	0,70mm	High
Neoprene Gloves	<0,4mm	High
Nitrile Gloves	0,38mm	High
<b>Non suitable Gloves - non exhaustive list (Permeation breakthrough times &lt; 10 min):</b>		
<b>Material:</b>	<b>Thickness (or less):</b>	
Natural Rubber Gloves	0,75mm	
Nitrile Gloves	0,31mm	
Neoprene Gloves	0,75mm	
Butyl Gloves	0,50mm	
PVA Gloves	0,2-0,3mm	

Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing.

USE PE gloves as under gloves for difficult situations like for instance: high exposure, unknown composition or unknown properties of the chemicals.

Eye/face protection



Use safety eyewear designed to protect against splash of liquids (EN166).



Product code: 255VR - Version 2 - Revision Date: 10-09-2019

Skin protection



Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

Do not allow to enter drains or water courses.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

- (a) Appearance : Liquid
- (b) Odour : Typical
- (c) Odour threshold : Testing not feasible due to nature of the product.
- (d) pH : Not applicable due to nature of the product.
- (e) Melting point/freezing point : Not applicable due to nature of the product.
- (f) Initial boiling point and boiling range : Not applicable due to nature of the product.
- (g) Flash point : 38°C Method: ASTM D3278-96 / ISO13736
- (h) Flammability (solid, gas) : Not applicable due to nature of the product.
- (i) Vapour density : Heavier than air
- (j) Relative density : 1,27 @ 20°C Method: ASTM D1475-98
- (k) Solubility(ies) : Not Soluble (in water).
- (l) Partition coefficient: n-octanol/water : Not applicable due to nature of the product.
- (m) Auto-ignition temperature / Decomposition temperature : Testing not feasible due to nature of the product.
- (n) Viscosity : >20,5 mm<sup>2</sup>/s @40°C (ISO3219-B)
- (o) Explosive properties : The product itself is not explosive, but the formation of an explosive mixture of vapour or dust with air is possible.
- (p) Oxidising properties : Not applicable due to nature of the product.

Substance name	(q) Explosive limits	(r) Evaporation rate	(s) Vapour pressure
Hydrocarbons, C10, Aromatics, <1% Naphthalene.	Not available	Not available	1 Kpa
Reaction Mass Of Ethylbenzene And Xylene.	1.0-7.0%	Not available	8.0 mbar
Isobutyl Methyl Ketone.	1.2-8.0%	1,6	25 mbar
Aluminium Powder (Stabilised).	Not available	Not available	Not available
Bis-[4-(2,3-Epoxypropoxy)Phenyl]Propane.	Not applicable	Not available	4.6x10-8 Pa
Naphtha (Petroleum), Hydrotreated Heavy.	0.6-7%	Not available	0,3 kPa
Methanol.	5.5-44%	Not available	128 mbar

**9.2. Other information**

No additional information

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No specific test data related to reactivity available for this product or its ingredients.

**10.2. Chemical stability**

Stable under recommended storage and handling conditions (see section 7).

**10.3. Possibility of hazardous reactions**

In combination with oxidizing agents, strongly alkaline and strongly acid materials, exothermic reactions and/or explosive reactions may occur or toxic vapours may arise.

**10.4. Conditions to avoid**

When exposed to high temperatures may produce hazardous decomposition products.

**10.5. Incompatible materials**

Keep away from oxidising agents, strongly alkaline and strongly acid materials.



Product code: 255VR - Version 2 - Revision Date: 10-09-2019

### 10.6. Hazardous decomposition products

Carbon monoxide and dioxide, smoke, oxides of nitrogen, hydrochloric acid etc.

## SECTION 11: Toxicological information

There are no data available on the mixture itself.

The mixture has been assessed following the additivity method of the CLP Regulation (EC) No 1272/2008 and classified for toxicological hazards accordingly.

See Sections 2 and 3 for details.

### 11.1. Information on toxicological effects

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin.

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

The liquid splashed in the eyes may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhoea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains Bis-[4-(2,3-Epoxypropoxy)Phenyl]Propane. May produce an allergic reaction.

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar mixtures, this mixture may be a skin sensitiser and an irritant. It contains low molecular weight epoxy constituents which are irritating to eyes, mucous membrane and skin. Repeated skin contact may lead to irritation and to sensitisation, possibly with cross-sensitisation to other epoxies. Skin contact with the mixture and exposure to spray mist and vapour should be avoided.

Substance name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Hydrocarbons, C10, Aromatics, <1% Naphthalene.	Not available.	Not available.	Not available.
Reaction Mass Of Ethylbenzene And Xylene.	>2000 mg/kg, Rat	>2000 mg/kg, Rat	29 mg/lRat,4h
Isobutyl Methyl Ketone.	2080 mg/kg, Rat	>2000 mg/kg, Rabbit	8,2-16,4 mg/lRat,4h
Aluminium Powder (Stabilised).	>2000 mg/kg, Rat	Not available.	888 mg/kgRat,4h
Bis-[4-(2,3-Epoxypropoxy)Phenyl]Propane.	>15000 mg/kg, Rabbit	23000 mg/kg, Rabbit	Not available.
Naphtha (Petroleum), Hydrotreated Heavy.	>5000 mg/kg, Rat	>5000 mg/kg, Rabbit	>5 mg/lRat,4h
Methanol.	5628 mg/kg, Rat	15800 mg/kg, Rabbit	2,8 mg/kgRat,4h

## Conclusion/Summary

### Acute Toxicity

ATEmix (oral) : No specific data.

ATEmix (Dermal) : No specific data.

ATEmix (Inhalation) : No specific data.



Product code: 255VR - Version 2 - Revision Date: 10-09-2019

**Skin corrosion/irritation:**

Conclusion/Summary on mixture : Causes skin irritation.  
: Method: Additivity approach, no testdata available.

**Serious eye damage/irritation:**

Conclusion/Summary on mixture : Causes serious eye irritation.  
: Method: Additivity approach, no testdata available.

**Respiratory or skin sensitization:**

Conclusion/Summary on mixture : May cause an allergic skin reaction.  
: Method: Concentration Limit, no testdata available.  
: No specific data on Respiratory sensitization.

**Germ cell mutagenicity:**

Conclusion/Summary on mixture : No specific data.

**Carcinogenicity:**

Conclusion/Summary on mixture : No specific data.

**Reproductive toxicity:**

Conclusion/Summary on mixture : No specific data.

**STOT - single exposure:**

Conclusion/Summary on mixture : No specific data.

**STOT - repeated exposure:**

Conclusion/Summary on mixture : May cause damage to organs through prolonged or repeated exposure.  
: Method: Concentration Limit, no testdata available.

**Aspiration hazard:**

Conclusion/Summary on mixture : No specific data.

**Information on likely routes of exposure**

Inhalation : Exposure to vapours may cause a health hazard.  
: Serious effects may be delayed following exposure.  
Ingestion : No specific data.  
Skin contact : Causes skin irritation.  
: May cause an allergic skin reaction.  
Eye contact : Causes serious eye irritation.

**Symptoms related to the physical, chemical and toxicological characteristics**

Inhalation : Adverse symptoms may include the following: Cough  
Ingestion : No specific data.  
Skin contact : Adverse symptoms may include the following: irritation, redness  
Eye contact : Adverse symptoms may include the following: irritation, watering, redness

**Delayed and immediate effects and also chronic effects from short and long term exposure****Short term exposure**

Potential immediate effects : No specific data.  
Potential delayed effects : No specific data.

**Long term exposure**

Potential immediate effects : No specific data.  
Potential delayed effects : No specific data.

**Potential chronic health effects**

Conclusion/Summary : Not available  
General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.  
Carcinogenicity : No known significant effects or critical hazards.  
Mutagenicity : No known significant effects or critical hazards.  
Teratogenicity : No known significant effects or critical hazards.  
Developmental effects : No known significant effects or critical hazards.  
Fertility effects : No known significant effects or critical hazards.  
Other information : Not available

Product code: 255VR - Version 2 - Revision Date: 10-09-2019

## SECTION 12: Ecological information

There are no data available on the mixture itself.

Do not allow to enter drains or water courses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified for eco-toxicological hazards.

### 12.1. Toxicity

Substance name	Results - Species - Exposure
Hydrocarbons, C10, Aromatics, <1% Naphthalene.	EC50/48h >=3<=10 mg/l (Daphnia magna), LC50/96h >=2<=5 mg/l (Oncorhynchus mykiss), IC50 - Not available
Reaction Mass Of Ethylbenzene And Xylene.	EC50/48h 1-10 mg/l (Daphnia magna), LC50/96h - 13.4 mg/l Fathead minnow, IC50/72h
Isobutyl Methyl Ketone.	EC50/48h 170 mg/l (Daphnia magna), LC50/96h 505 mg/l (Pimephales promelas), IC50/16h >100 mg/l (Scenedesmus subspicatus)
Aluminium Powder (Stabilised).	EC50 - Not available, LC50 - Not available, IC50 - Not available
Bis-[4-(2,3-Epoxypropoxy)Phenyl]Propane.	EC50/48h 1,8 mg/l (Daphnia magna), LC50/96h 2 mg/l (Oncorhynchus mykiss), IC50/8h >42,6 mg/l (Bacteria)
Naphtha (Petroleum), Hydrotreated Heavy.	EC50/48h >1000 mg/l (Daphnia magna), LC50/96h >1000 mg/l (Oncorhynchus mykiss), IC50 - Not available
Methanol.	EC50 - Not available, LC50/96h 7900-27700 mg/l (fish), IC50 - Not available

### 12.2. Persistence and degradability

Conclusion/Summary : Not available

### 12.3. Bioaccumulative potential

Substance name	LogPow	BCF	Potential
Hydrocarbons, C10, Aromatics, <1% Naphthalene.	Not available	Not available	Not available
Reaction Mass Of Ethylbenzene And Xylene.	3,1	25,9	Low
Isobutyl Methyl Ketone.	1,31	Not available	Low
Aluminium Powder (Stabilised).	Not available	Not available	Not available
Bis-[4-(2,3-Epoxypropoxy)Phenyl]Propane.	3,242	31 L/kg ww	Not available
Naphtha (Petroleum), Hydrotreated Heavy.	5-6,7	Not available	Not available
Methanol.	-0,74	<10	Low

### 12.4. Mobility in soil

Soil/water partition coefficient (KOC) : Not available

Mobility : Not available

### 12.5. Results of PBT and vPvB assessment

Not available

### 12.6. Other adverse effects

Not available

Product code: 255VR - Version 2 - Revision Date: 10-09-2019

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

Dispose of containers contaminated by the product in accordance with local or national legal provisions. The European Waste Catalogue classification of this product, when disposed of as waste is 08 01 11. If this product is mixed with other wastes, this code may no longer apply. If mixed with other wastes, the appropriate code should be assigned. For further information contact your local waste authority. Do not allow into drains or water courses or dispose of where ground or surface waters may be affected. Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.


Containers which are not properly cleaned may contain (highly) flammable or explosive vapours.

Special precautions:

Use appropriate protective equipment for the removal and / or disposal of this product.

**SECTION 14: Transport information**

Transport in accordance with ADR/RID/ADN, IMDG and ICAO/IATA.

	ADR/RID/ADN	IMDG	IATA
14.1. UN number	UN 1263	UN 1263	UN 1263
14.2. UN proper shipping name	PAINT	PAINT	PAINT
14.3. Transport hazard class(es)	Carriage in accordance with 2.2.3.1.5	Transport in accordance with 2.3.2.5 of the IMDG Code (<30L)	3
Hazard labels			
14.4. Packing group	III	III	III
14.5. Environmental hazards	No	No Marine Pollutant: No	No
Additional information	Hazard Identification Number: -	EmS: F-E, S-E	The "viscosity exemption" provision does not apply to air transport.

**14.6. Special precautions for user**

Transport within the user's premises:  
 Always transport in closed containers that are upright and secure.  
 Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.



Product code: 255VR - Version 2 - Revision Date: 10-09-2019

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

The information in this Safety Data Sheet is required pursuant to

\* Annex II to regulation (EC) No 1907/2006 and its amendments.

\* the provisions of the Health and Safety at Work etc. Act [and the Control of Substances Hazardous to Health Regulations] apply to the use of this product at work.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.

**15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

**SECTION 16: Other information**

**The product is classified and labelled for supply in accordance with Regulation (EC) No 1272/2008.**

**Rationale:**

H226	Measured
H315	Additivity approach
H319	Additivity approach
H317	Concentration limit
H335	Additivity approach
H373	Concentration limit
H412	Summation method

**Abbreviations and acronyms:**

ADR	: European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN	: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ATE	: Acute Toxicity Estimate
BCF	: Bioconcentration factor
CLP	: Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DNEL	: Derived No Effect Level
IATA	: International Air Transport Association
IMDG	: International Maritime Dangerous Goods
Kow	: octanol-water partition coefficient
LC50	: Lethal Concentration to 50 % of a test population
LD50	: Lethal Dose to 50% of a test population (Median Lethal Dose)
PBT	: Persistent, Bioaccumulative and Toxic substance
PNEC	: Predicted No Effect Concentration(s)
RID	: Regulations concerning the International Carriage of Dangerous Goods by Rail
STOT	: Specific Target Organ Toxicity
vPvB	: Very Persistent and Very Bioaccumulative
Note W	: It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.



Product code: 255VR - Version 2 - Revision Date: 10-09-2019

**Full text of Hazard Statements appearing in Section 3.2:**

- EUH066 Repeated exposure may cause skin dryness or cracking.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H261 In contact with water releases flammable gases.
- H301 Toxic if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317-(1B) May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H370\*\* Causes damage to organs.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

Amendments: 10-09-2019, §2,3,8,9,11,12&amp;16

The information of this SDS is based on the present state of our knowledge and on current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. Unless indicated elsewhere in this safety data sheet, the classification of this mixture has been determined using a combination of test data, bridging principles and calculation.