

WESSEX

RESINS+ADHESIVES

SAFETY DATA SHEET WEST SYSTEM 105 RESIN

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name WEST SYSTEM 105 RESIN

Product number 105

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Resin.

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Wessex Resins & Adhesives
Cupernham House
Cupernham Lane
Romsey
Hampshire
S051 7LF
Tel+44(0)1794 521111
Fax+44(0)1794 521271
info@wessex-resins.com

1.4. Emergency telephone number

Emergency telephone +44(0)207 858 1228

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317


Environmental hazards Aquatic Chronic 2 - H411

Human health The liquid is irritating to eyes and skin. The product contains a sensitising substance. See Section 11 for additional information on health hazards.

Environmental The product contains a substance which may have hazardous effects on the environment.

2.2. Label elements

Pictogram



WEST SYSTEM 105 RESIN

Signal word	Warning
Hazard statements	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	P102 Keep out of reach of children. P273 Avoid release to the environment. P280 Wear protective gloves, eye and face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/ attention. P501 Dispose of contents/ container in accordance with national regulations.
Contains	Epoxy resin (Number average MW <= 700), BISPHENOL F EPOXY RESIN
Supplementary precautionary statements	P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Epoxy resin (Number average MW <= 700)	60-100%
CAS number: 25068-38-6	EC number: 500-033-5
	REACH registration number: 01-2119456619-26-0000
Classification	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Skin Sens. 1 - H317	
Aquatic Chronic 2 - H411	
Benzyl alcohol	10-30%
CAS number: 100-51-6	EC number: 202-859-9
	REACH registration number: 01-2119492630-38-XXXX
Classification	
Acute Tox. 4 - H302	
Acute Tox. 4 - H332	
Eye Irrit. 2 - H319	

WEST SYSTEM 105 RESIN

BISPHENOL F EPOXY RESIN		1-5%
CAS number: 9003-36-5	EC number: 500-006-8	REACH registration number: 01-2119454392-40-0000
Classification		
Skin Irrit. 2 - H315		
Eye Irrit. 2 - H319		
Skin Sens. 1 - H317		
Aquatic Chronic 2 - H411		
isobutanol		<1%
CAS number: 78-83-1	EC number: 201-148-0	REACH registration number: 01-2119484609-23-XXXX
Classification		
Flam. Liq. 3 - H226		
Skin Irrit. 2 - H315		
Eye Dam. 1 - H318		
STOT SE 3 - H335, H336		

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Ingestion	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
Skin contact	It is important to remove the substance from the skin immediately. In the event of any sensitisation symptoms developing, ensure further exposure is avoided. Remove contamination with soap and water or recognised skin cleansing agent. Get medical attention if symptoms are severe or persist after washing.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue. If it is suspected that volatile contaminants are still present around the affected person, first aid personnel should wear an appropriate respirator or self-contained breathing apparatus. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

WEST SYSTEM 105 RESIN

4.2. Most important symptoms and effects, both acute and delayed

General information	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Prolonged inhalation of high concentrations may damage respiratory system.
Ingestion	May cause discomfort if swallowed.
Skin contact	May cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to skin.
Eye contact	Irritating to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically. May cause sensitisation or allergic reactions in sensitive individuals.
-----------------------------	------------------------------------------------------------------------------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. Carbon dioxide (CO ₂). Carbon monoxide (CO).

5.3. Advice for firefighters

Protective actions during firefighting	Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Avoid contact with skin and eyes.
-----------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

6.2. Environmental precautions

Environmental precautions	Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).
----------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

6.3. Methods and material for containment and cleaning up

WEST SYSTEM 105 RESIN

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Small Spillages: Collect spillage. Large Spillages: Absorb spillage with non-combustible, absorbent material. The contaminated absorbent may pose the same hazard as the spilled material. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Avoid discharge to the aquatic environment. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep away from heat, sparks and open flame. Protect from light. Store away from the following materials: Acids. Alkalis. Oxidising materials.

Storage class

Miscellaneous hazardous material storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

isobutanol

Long-term exposure limit (8-hour TWA): WEL 50 ppm 154 mg/m³

Short-term exposure limit (15-minute): WEL 75 ppm 231 mg/m³

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Good general ventilation should be adequate to control worker exposure to airborne contaminants.

WEST SYSTEM 105 RESIN

Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended. Wear protective gloves made of the following material: Nitrile rubber. Thickness: ≥ 0.13 mm The selected gloves should have a breakthrough time of at least 0.5 hours.
Other skin and body protection	Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
Hygiene measures	Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. When using do not eat, drink or smoke. Wash at the end of each work shift and before eating, smoking and using the toilet. Warn cleaning personnel of any hazardous properties of the product.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Combination filter, type A2/P2.
Environmental exposure controls	Avoid discharge to the aquatic environment. Keep container tightly sealed when not in use.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Clear liquid.
Colour	Light (or pale). Amber.
Odour	Mild.
Odour threshold	Not determined.
pH	Not determined.
Melting point	Not determined.
Initial boiling point and range	Not determined.
Flash point	> 100°C Closed cup.
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	1.16 @ 20°C
Bulk density	Not determined.
Solubility(ies)	Slightly soluble in water.

WEST SYSTEM 105 RESIN

Partition coefficient	Not determined.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	Not determined.
Explosive properties	Not determined.
Oxidising properties	Does not meet the criteria for classification as oxidising.

9.2. Other information

Other information	Not known.
--------------------------	------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---------------------------------------------------------------------

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---------------------------------------------------------------------

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	None known.
-------------------------------------------	-------------

10.4. Conditions to avoid

Conditions to avoid	There are no known conditions that are likely to result in a hazardous situation.
----------------------------	-----------------------------------------------------------------------------------

10.5. Incompatible materials

Materials to avoid	Strong acids. Strong oxidising agents.
---------------------------	----------------------------------------

10.6. Hazardous decomposition products

Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.
-----------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀)	Based on available data the classification criteria are not met.
-------------------------------------	------------------------------------------------------------------

ATE oral (mg/kg)	10,771.28
-------------------------	-----------

Acute toxicity - dermal

Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.
---------------------------------------	------------------------------------------------------------------

Acute toxicity - inhalation

Notes (inhalation LC₅₀)	Based on available data the classification criteria are not met.
-------------------------------------------	------------------------------------------------------------------

ATE inhalation (dusts/mists mg/l)	21.92
------------------------------------------	-------

Skin corrosion/irritation

Animal data	Irritating.
--------------------	-------------

Serious eye damage/irritation

Serious eye damage/irritation	Causes serious eye irritation.
--------------------------------------	--------------------------------

WEST SYSTEM 105 RESIN

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation May cause skin sensitisation or allergic reactions in sensitive individuals.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity

None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation

Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion

May cause sensitisation or allergic reactions in sensitive individuals. May cause irritation.

Skin contact

May cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to skin.

Eye contact

Irritating to eyes.

Route of exposure

Ingestion Inhalation Skin and/or eye contact

Target organs

No specific target organs known.

Medical considerations

Skin disorders and allergies.

Toxicological information on ingredients.

Epoxy resin (Number average MW <= 700)

Acute toxicity - oral

Notes (oral LD₅₀) > 2000 mg/kg Rat REACH dossier information. Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) > 2000 mg/kg Rat REACH dossier information. Based on available data the classification criteria are not met.

WEST SYSTEM 105 RESIN

Skin corrosion/irritation

Animal data

Dose: 0.5ml, 4 hr, Rabbit Erythema/eschar score: Very slight erythema - barely perceptible (1). Oedema score: Very slight oedema - barely perceptible (1). REACH dossier information. Irritating to skin.

Skin sensitisation

Skin sensitisation

Local Lymph Node Assay (LLNA) - Mouse: Sensitising. REACH dossier information. May cause sensitisation by skin contact.

Germ cell mutagenicity

Genotoxicity - in vitro

Gene mutation: Negative. REACH dossier information. Based on available data the classification criteria are not met.

Genotoxicity - in vivo

Chromosome aberration: Negative. REACH dossier information. This substance has no evidence of mutagenic properties.

Carcinogenicity

Carcinogenicity

NOAEL 100 mg/kg, Oral, Rat REACH dossier information. There is no evidence that the product can cause cancer.

Reproductive toxicity

Reproductive toxicity - fertility

Two-generation study - NOAEL 20 mg/kg/day, Oral, Rat P REACH dossier information. Based on available data the classification criteria are not met.

Reproductive toxicity - development

Maternal toxicity: - NOAEL: 180 mg/kg/day, Oral, Rat REACH dossier information. Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 50 mg/kg, Oral, Rat REACH dossier information. Not classified as a specific target organ toxicant after repeated exposure.

Benzyl alcohol

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 1,620.0

Species Rat

Notes (oral LD₅₀) REACH dossier information. Harmful if swallowed.

ATE oral (mg/kg) 1,620.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ dust/mist mg/l) 3.297

Species Rat

Notes (inhalation LC₅₀) 4 hours, Aerosol., Rat REACH dossier information. Harmful if inhaled.

ATE inhalation (dusts/mists mg/l) 3.297

Skin corrosion/irritation

Animal data

Dose: 0.5ml, 4 hr, Rabbit Erythema/eschar score: No erythema (0). Oedema score: No oedema (0). REACH dossier information. Not irritating.

WEST SYSTEM 105 RESIN

Serious eye damage/irritation

Serious eye damage/irritation Dose: 0.1 ml, 24 hours, Rabbit Cornea score: 1 Iris score: 0 Conjunctivae score: 2 Chemosis score: 1 REACH dossier information. Causes serious eye irritation.

Skin sensitisation

Skin sensitisation Draize test: - Guinea pig: Not sensitising. REACH dossier information.

Germ cell mutagenicity

Genotoxicity - in vitro Chromosome aberration: Negative. REACH dossier information.

Genotoxicity - in vivo Chromosome aberration: Negative. REACH dossier information.

Reproductive toxicity

Reproductive toxicity - development Developmental toxicity: - NOAEL: 550 mg/kg/day, Oral, Mouse REACH dossier information.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 400 mg/kg, Oral, Rat REACH dossier information.

BISPHENOL F EPOXY RESIN

Toxicological effects No information available.

isobutanol

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 3,350.0

Species Rat

Notes (oral LD₅₀) REACH dossier information. Based on available data the classification criteria are not met.

ATE oral (mg/kg) 3,350.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,460.0

Species Rabbit

Notes (dermal LD₅₀) REACH dossier information. Based on available data the classification criteria are not met.

ATE dermal (mg/kg) 2,460.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 24.6

Species Rat

Notes (inhalation LC₅₀) REACH dossier information. Based on available data the classification criteria are not met.

WEST SYSTEM 105 RESIN

ATE inhalation (vapours mg/l)	24.6
<u>Skin corrosion/irritation</u>	
Animal data	Dose: 0.5ml, 24 hr, Rabbit Erythema/eschar score: No erythema (0). Oedema score: Slight oedema - edges of area well defined by definite raising (2). REACH dossier information. Irritating to skin.
<u>Skin sensitisation</u>	
Skin sensitisation	Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising. Estimated value. REACH dossier information. Epidemiological studies have shown no evidence of skin sensitisation.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Genome mutation:: Negative. REACH dossier information. Based on available data the classification criteria are not met.
Genotoxicity - in vivo	Chromosome aberration: Negative. REACH dossier information. This substance has no evidence of mutagenic properties.
<u>Carcinogenicity</u>	
Carcinogenicity	There is no evidence that the product can cause cancer.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Two-generation study - NOAEL 7.5 mg/l, Inhalation, Rat P REACH dossier information. Based on available data the classification criteria are not met.
Reproductive toxicity - development	Maternal toxicity: - NOAEL: 10 mg/l, Inhalation, Rat REACH dossier information. Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	NOAEL 1450 mg/kg, Oral, Rat REACH dossier information. Not classified as a specific target organ toxicant after repeated exposure.

SECTION 12: Ecological Information

Ecotoxicity Dangerous for the environment if discharged into watercourses.

12.1. Toxicity

Toxicity Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.

Ecological information on ingredients.

Epoxy resin (Number average MW <= 700)

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: 1.2 mg/l, Oncorhynchus mykiss (Rainbow trout) REACH dossier information.
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 2.8 mg/l, Daphnia magna REACH dossier information.
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: 9.4 mg/l, Selenastrum capricornutum REACH dossier information.
Acute toxicity - microorganisms	IC ₅₀ , 3 hours >: 100 mg/l, Activated sludge REACH dossier information.

WEST SYSTEM 105 RESIN

Benzyl alcohol

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: 460 mg/l, Pimephales promelas (Fat-head Minnow) REACH dossier information.
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 230 mg/l, Daphnia magna REACH dossier information.
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: 770 mg/l, Freshwater algae REACH dossier information.
Acute toxicity - microorganisms	EC ₅₀ , 48 hours: 2100 mg/l, Activated sludge REACH dossier information.

BISPHENOL F EPOXY RESIN

Toxicity	There are no data on the ecotoxicity of this product.
-----------------	-------------------------------------------------------

isobutanol

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: 1430 mg/l, Pimephales promelas (Fat-head Minnow) REACH dossier information.
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 1100 mg/l, Freshwater invertebrates REACH dossier information.
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: 1799 mg/l, Freshwater algae REACH dossier information.

12.2. Persistence and degradability

Persistence and degradability The product is not readily biodegradable.

Ecological information on ingredients.

Epoxy resin (Number average MW <= 700)

Phototransformation	Water - DT ₅₀ : 6.44 hours Estimated value. REACH dossier information.
Biodegradation	Water - Degradation (%) 5: 28 days REACH dossier information. No biodegradation observed under test conditions.

Benzyl alcohol

Biodegradation	- Degradation (%) 92: 14 days REACH dossier information. The substance is readily biodegradable.
-----------------------	--------------------------------------------------------------------------------------------------------

BISPHENOL F EPOXY RESIN

Biodegradation	Not determined.
-----------------------	-----------------

isobutanol

WEST SYSTEM 105 RESIN

Phototransformation	Water - DT ₅₀ : 56 hours Estimated value. REACH dossier information.
Biodegradation	Water - Degradation (%) 70: 28 days REACH dossier information. The substance is readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

Ecological information on ingredients.

Epoxy resin (Number average MW <= 700)

Bioaccumulative potential	The product is not bioaccumulating. BCF: ~ 31, Estimated value. REACH dossier information.
Partition coefficient	log Pow: ≥ 2.918 REACH dossier information.

Benzyl alcohol

Bioaccumulative potential	No data available on bioaccumulation.
Partition coefficient	log Pow: 1.1 REACH dossier information.

BISPHENOL F EPOXY RESIN

Bioaccumulative potential No data available on bioaccumulation.

isobutanol

Bioaccumulative potential	No data available on bioaccumulation.
Partition coefficient	log Pow: 1 REACH dossier information.

12.4. Mobility in soil

Mobility No information available.

Ecological information on ingredients.

Epoxy resin (Number average MW <= 700)

Mobility	Slightly soluble in water.
Adsorption/desorption coefficient	Water - log Koc: ~ 2.65 @ 20°C Estimated value. REACH dossier information.
Surface tension	58.7 mN/m @ 20°C REACH dossier information.

Benzyl alcohol

Mobility The product is soluble in water.

BISPHENOL F EPOXY RESIN

Mobility No information available.

WEST SYSTEM 105 RESIN

isobutanol

Mobility	The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.
Henry's law constant	~ 1.012 Pa m ³ /mol @ 25°C Estimated value. REACH dossier information.
Surface tension	69.7 mN/m @ 20°C REACH dossier information.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

Epoxy resin (Number average MW <= 700)

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

Benzyl alcohol

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

BISPHENOL F EPOXY RESIN

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

isobutanol

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

Ecological information on ingredients.

BISPHENOL F EPOXY RESIN

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information The generation of waste should be minimised or avoided wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

WEST SYSTEM 105 RESIN

Disposal methods Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Incineration or landfill should only be considered when recycling is not feasible. Do not discharge into drains or watercourses or onto the ground.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	3082
UN No. (IMDG)	3082
UN No. (ICAO)	3082
UN No. (ADN)	3082

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Epoxy resin (Number average MW <= 700), BISPHENOL F EPOXY RESIN)
Proper shipping name (IMDG)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Epoxy resin (Number average MW <= 700), BISPHENOL F EPOXY RESIN)
Proper shipping name (ICAO)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Epoxy resin (Number average MW <= 700), BISPHENOL F EPOXY RESIN)
Proper shipping name (ADN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Epoxy resin (Number average MW <= 700), BISPHENOL F EPOXY RESIN)

14.3. Transport hazard class(es)

ADR/RID class	9
ADR/RID classification code	M6
ADR/RID label	9
IMDG class	9
ICAO class/division	9
ADN class	9

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ADN packing group	III
ICAO packing group	III

14.5. Environmental hazards

WEST SYSTEM 105 RESIN

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS	F-A, S-F
ADR transport category	3
Emergency Action Code	•3Z
Hazard Identification Number (ADR/RID)	90
Tunnel restriction code	(-)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Health and Safety at Work etc. Act 1974 (as amended). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"]. EH40/2005 Workplace exposure limits.
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Commission Regulation (EU) No 2015/830 of 28 May 2015. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

WEST SYSTEM 105 RESIN

Abbreviations and acronyms used in the safety data sheet	<p>ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.</p> <p>ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.</p> <p>RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.</p> <p>IATA: International Air Transport Association.</p> <p>ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.</p> <p>IMDG: International Maritime Dangerous Goods.</p> <p>CAS: Chemical Abstracts Service.</p> <p>ATE: Acute Toxicity Estimate.</p> <p>LC₅₀: Lethal Concentration to 50 % of a test population.</p> <p>LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).</p> <p>EC₅₀: 50% of maximal Effective Concentration.</p> <p>PBT: Persistent, Bioaccumulative and Toxic substance.</p> <p>vPvB: Very Persistent and Very Bioaccumulative.</p>
Classification abbreviations and acronyms	<p>Eye Irrit. = Eye irritation</p> <p>Skin Irrit. = Skin irritation</p> <p>Skin Sens. = Skin sensitisation</p> <p>Aquatic Chronic = Hazardous to the aquatic environment (chronic)</p>
Key literature references and sources for data	<p>Source: European Chemicals Agency, http://echa.europa.eu/</p>
Classification procedures according to Regulation (EC) 1272/2008	<p>Skin Irrit. 2 - H315: Eye Irrit. 2 - H319: Skin Sens. 1 - H317: : Expert judgement. Aquatic Chronic 2 - H411: : Expert judgement.</p>
Training advice	<p>Read and follow manufacturer's recommendations. Only trained personnel should use this material.</p>
Revision date	13/06/2018
Revision	6
Supersedes date	24/05/2018
SDS number	10015
Hazard statements in full	<p>H226 Flammable liquid and vapour.</p> <p>H302 Harmful if swallowed.</p> <p>H315 Causes skin irritation.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H318 Causes serious eye damage.</p> <p>H319 Causes serious eye irritation.</p> <p>H332 Harmful if inhaled.</p> <p>H335 May cause respiratory irritation.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.