

# SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

#### SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name : PB 250 Product code : 765. EPOXY RESIN UFI : 4EK5-J094-J002-CK3V

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Epoxy resin

Uses advised against : data not available

#### 1.3. Details of the supplier of the safety data sheet

Registered company name : SICOMIN Composites.

Address : 31 avenue de la Lardiere - BP 23.13161.Chateauneuf les Martigues.France.

Telephone : +33 (0)4 42 42 30 20. Fax : +33 (0)4 42 81 29 29.

composites@sicomin.com

Site web : http://www.sicomin.com

AUSTRALIAN Importer : Lavender CE Pty Ltd - 108 Westgate Street - Wacol, Qld, 4076 AUSTRALIA / M: 0409 892 032 / Ph: +61 7 3255 6924 / Fax: +61 7 3255 6923 / Web: www.lavender-ce.com / Email: sheading@lavender-ce.com

#### 1.4. Emergency telephone number : .

Association/Organisation : INRS / ORFILA tél: +33(0)1.45.42.59.59 - (FRANCE) .

#### Other emergency numbers

Health and Safety Executive (HSE) Chemicals Regulation Directorate - Telephone: +44 151 951 3317 - USA : +1/ 800/ 424.9300 - AUSTRALIA : Emergency Poison Advice : 131 126

# **SECTION 2 : HAZARDS IDENTIFICATION**

# 2.1. Classification of the substance or mixture

# In compliance with EC regulation No. 1272/2008 and its amendments.

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Hazardous to the aquatic environment - Chronic hazard, Category 2 (Aquatic Chronic 2, H411).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

#### 2.2. Label elements

# In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



Signal Word : WARNING Product identifiers : EC 701-263-0 EC 216-823-5 Additional labeling : EUH205 Hazard statements :

FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL 2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE

Contains epoxy constituents. May produce an allergic reaction.

250 - 765	
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
Precautionary statements -	General :
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
Precautionary statements -	Prevention :
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/
Precautionary statements -	 Response ·
P362 + P364	Take off contaminated clothing and wash it before reuse.
Precautionary statements -	5
P501	Dispose of contents/container to hazardous waste.

#### 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006. The mixture does not contain substances> = 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission. May evolve hydrogen on contact with alcohols, organic acids and bases.

#### SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

# 3.2. Mixtures

# **Composition :**

Identification	Classification (EC) 1272/2008	Note	%
EC: 701-263-0	GHS07, GHS09		50 <= x % < 100
REACH: 01-2119454392-40-XXXX	Wng		
	Skin Irrit. 2, H315		
FORMALDEHYDE, OLIGOMERIC	Skin Sens. 1, H317		
REACTION PRODUCTS WITH	Aquatic Chronic 2, H411		
1-CHLORO-2,3-EPOXYPROPANE AND			
PHENOL			
CAS: 1675-54-3	GHS07, GHS09		25 <= x % < 50
EC: 216-823-5	Wng		
REACH: 01-2119456619-26-XXXX	Skin Irrit. 2, H315		
	Skin Sens. 1, H317		
2,2'-[(1-METHYLETHYLIDENE)BIS(4	Eye Irrit. 2, H319		
,1-PHENYLENEOXYMETHYLENE)]BISOX	Aquatic Chronic 2, H411		
IRANE			

Identification	Specific concentration limits	ATE
CAS: 1675-54-3	Skin Irrit. 2: H315 >=5%	dermal: ATE = 2000 mg/kg BW
EC: 216-823-5	Eye Irrit. 2: H319 C>= 5%	oral: ATE = 11400 mg/kg BW
REACH: 01-2119456619-26-XXXX		
2,2'-[(1-METHYLETHYLIDENE)BIS(4 ,1-PHENYLENEOXYMETHYLENE)]BISOX		
IRANE		

# Information on ingredients :

(Full text of H-phrases: see section 16)

#### **SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor. NEVER induce swallowing by an unconscious person.

#### 4.1. description of first aid measures

#### In the event of exposure by inhalation :

If inhaled, move the patient to fresh air and keep warm and rest.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

Flush with large amounts of water. Remove contact lenses if the victim is. Continue to rinse. Seek medical attention if symptoms persist.

# In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated aera is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

# In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor. Seek medical attention immediately, showing the label.

# 4.2. Most important symptoms and effects, both acute and delayed

No data available

# 4.3. Indication of any immediate medical attention and special treatment needed

# Information for the doctor :

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person

may need to remain under medical supervision for 48 hours.

Contact a specialist for treatment poisoning if large quantities have been ingested or inhaled.

# **SECTION 5 : FIREFIGHTING MEASURES**

Non-flammable.

# 5.1. Extinguishing media

# Suitable methods of extinction

- In the event of a fire, use :
- carbon dioxide (CO2)
- sprayed water or water mist
- foam

# Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

# 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health. Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO2)

# 5.3. Advice for firefighters

Firefighters should wear suitable protective clothing and a respirator mask with self- full operated in positive pressure mode. Wear conform with the European standard EN 469.

# **SECTION 6 : ACCIDENTAL RELEASE MEASURES**

# 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

# For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

#### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

# 6.3. Methods and material for containment and cleaning up

# Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

# **SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled. Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

# 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Caution when opening, potential internal pressure.

# Fire prevention :

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :** 

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid skin and eye contact with this mixture.

# Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

# 7.2. Conditions for safe storage, including any incompatibilities

No data available.

#### Storage

Keep out of reach of children.

Store in original container protected from direct sunlight in a dry, cool and well ventilated area away from heat sources. Keep container tightly closed in a dry place.

Store away from heat and cold.

# Packaging

Always keep in packaging made of an identical material to the original.

# 7.3. Specific end use(s)

Suggested application : Foaming Epoxy

# SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

# 8.1. Control parameters

#### No data available.

#### Derived no effect level (DNEL) or derived minimum effect level (DMEL):

2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE (CAS: 1675-54-3)

Final use: Exposure method: Potential health effects: DNEL :

Final use: Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects:

Workers. Dermal contact. Short term systemic effects. 8.3 mg/kg body weight/day

Dermal contact. Long term systemic effects. 8.3 mg/kg body weight/day

Inhalation. Short term systemic effects. 12.3 mg of substance/m3

Inhalation. Long term systemic effects. 12.3 mg of substance/m3

# Consumers.

Ingestion. Short term systemic effects. 0.75 mg/kg body weight/day

Ingestion. Long term systemic effects. 0.75 mg/kg body weight/day

Dermal contact. Short term systemic effects.

# SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) PB 250 - 765

DNEL :

Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

# Final use: Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

# Final use: Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects:

DNEL :

Exposure method: Potential health effects: DNEL :

# Predicted no effect concentration (PNEC):

FI	edicted no effect concentration (FNEC).	
	2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEO>	(YMETHYLENE)]BISOXIRANE (CAS: 1675-54-3)
	Environmental compartment:	Soil.
	PNEC :	0.065 mg/kg
	Environmental compartment:	Fresh water.
	PNEC :	6 µg/l
	Environmental compartment:	Sea water.
	PNEC :	1 µg/l
	Environmental compartment:	Intermittent waste water.
	PNEC :	0.013 mg/l
	Environmental compartment:	Fresh water sediment.
	PNEC :	0.341 mg/kg
	Environmental compartment:	Marine sediment.
	PNEC :	0.034 mg/kg
	Environmental compartment:	Waste water treatment plant.
	PNEC :	10 mg/l

3.6 mg/kg body weight/day

Dermal contact. Long term systemic effects. 3.6 mg/kg body weight/day

Inhalation. Short term systemic effects. 0.75 mg of substance/m3

Inhalation. Long term systemic effects. 0.75 mg of substance/m3

#### FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL

Workers. Dermal contact. Short term local effects. 8.3 µg of substance/cm2

Dermal contact. Long term systemic effects. 104.15 mg/kg body weight/day

Inhalation. Long term systemic effects. 29.39 mg of substance/m3

# Man exposed via the environment.

Ingestion. Long term systemic effects. 6.25 mg/kg body weight/day

Dermal contact. Long term systemic effects. 62.5 mg/kg body weight/day

Inhalation. Long term systemic effects. 8.7 mg of substance/m3

# FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL Environmental compartment: Soil.

0.237 mg/kg

Fresh water. 0.003 mg/l

Sea water.

0.0003 mg/l

0.0254 mg/l

0.294 mg/kg

Marine sediment.

0.0294 mg/kg

Environmental compartment:
PNEC :

PNEC :

Environmental compartment: PNEC :

Waste water treatment plant. 10 mg/l

Intermittent waste water.

Fresh water sediment.

# 8.2. Exposure controls

Use only with adequate ventilation or provided with ventilation at the source.

#### Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

#### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

# - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Butyl Rubber (Isobutylene-isoprene copolymer)
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

# Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact. Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

Attention! If the protection group is insufficient.

Mask with filter type A, B, E, K, P for mixing with the hardener

# SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

# 9.1. Information on basic physical and chemical properties

Physical state	
Physical state :	Viscous liquid.
Colour	
Color :	white
Odour	WINC
Odour threshold :	Not stated.
	Not stated.
Melting point	Neteslevent
Melting point/melting range :	Not relevant.
Freezing point	
Freezing point / Freezing range :	Not stated.
Boiling point or initial boiling point and boiling range	
Boiling point/boiling range :	Not relevant.
Flammability	
Flammability (solid, gas):	Not stated.
Lower and upper explosion limit	
Explosive properties, lower explosivity limit (%) :	Not stated.
Explosive properties, upper explosivity limit (%):	Not stated.
Flash point	
Flash Point Interval :	FP > 100°C.
Auto-ignition temperature	
Self-ignition temperature :	Not relevant.
Decomposition temperature	
Decomposition point/decomposition range :	Not relevant.
pH	
pH (aqueous solution) :	Not stated.
pH :	Not relevant.
Kinematic viscosity	
Viscosity :	12 000 ± 2 400 mPa.s @ 25°C
Solubility	
Water solubility :	Insoluble.
Fat solubility :	Not stated.
Partition coefficient n-octanol/water (log value)	
Partition coefficient: n-octanol/water :	Not stated.
Vapour pressure	
Vapour pressure (50°C) :	Not relevant.
Density and/or relative density	
Density :	1.19 ± 0.02 @ 20°C
Relative vapour density	
Vapour density :	Not stated.
9.2. Other information	1401 Stateu.
	1 5600 + 0 002 @ 25 °C
Index of refraction : % VOC :	1.5690 ± 0.002 @ 25 °C 0
	U
9.2.1. Information with regard to physical hazard classes	
No data available.	
9.2.2. Other safety characteristics	
No data available.	
Miscibility	
Miscibility :	solvants aromatiques

# SECTION 10 : STABILITY AND REACTIVITY

#### 10.1. Reactivity

No data available.

#### 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

# 10.3. Possibility of hazardous reactions

No data available.

# 10.4. Conditions to avoid

Avoid :

- heat

# - flames and hot surfaces

# 10.5. Incompatible materials

No data available.

#### 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO2)

# SECTION 11 : TOXICOLOGICAL INFORMATION

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

May cause an allergic reaction by skin contact.

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar preparations, this preparation may be a skin sensitiser and a respiratory tract sensitiser as well as an irritant.

Constituents with a low molecular weight irritate the eyes, mucous membranes and the skin

Repeated contact with the skin may cause irritation and hypersensitisation, possibly in combination with other epoxide compounds.

# 11.1.1. Substances

#### Acute toxicity :

2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENE Oral route :	OXYMETHYLENE)]BISOXIRANE (CAS: 1675-54-3) LD50 = 11400 mg/kg bodyweight/day Species : Rat
Dermal route :	LD50 = 2000 mg/kg bodyweight/day Species : Rat
FORMALDEHYDE, OLIGOMERIC REACTION PROD Oral route :	DUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL LD50 > 2000 mg/kg bodyweight/day Species : Rat
Dermal route :	LD50 > 2000 mg/kg bodyweight/day Species : Rabbit
Skin corrosion/skin irritation : 2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENE	OXYMETHYLENE)]BISOXIRANE (CAS: 1675-54-3) Species : Rabbit OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
FORMALDEHYDE, OLIGOMERIC REACTION PROD	DUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL Species : Rabbit OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Serious damage to eyes/eye irritation : FORMALDEHYDE, OLIGOMERIC REACTION PROD Conjunctival redness :	OUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL Average score = 0 Species : Rabbit
Conjunctival oedema :	Average score = 0

	Species : Rabbit
	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Respiratory or skin sensitisation :	
	CTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL
Buehler Test :	Sensitiser.
	Species : Guinea pig
Germ cell mutagenicity :	
FORMALDEHYDE, OLIGOMERIC REAC	CTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL
Mutagenesis (in vivo) :	Negative.
	Species : Mouse
	Species : Bacteria
Ames test (in vitro) :	Positive.
Carcinogenicity :	
FORMALDEHYDE, OLIGOMERIC REAC	CTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL
Carcinogenicity Test :	Negative.
	No carcinogenic effect.
	Species : Mouse
	Other guideline
Reproductive toxicant :	
FORMALDEHYDE, OLIGOMERIC REAC	CTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL
No toxic effect for reproduction	
Study on development :	Species : Rabbit
	Other guideline
11.1.2. Mixture	
Respiratory or skin sensitisation :	
Contains epoxy compounds. May cause a	In allergic reaction.
11.2. Information on other hazards	
Monograph(s) from the IARC (Internation	al Agency for Research on Cancer) :
CAS 1675-54-3 : IARC Group 3 : The age	ent is not classifiable as to its carcinogenicity to humans.
ECTION 12 : ECOLOGICAL INFORMA	
Toxic to aquatic life with long lasting effect The product must not be allowed to run in	
•	to drains of waterways.
12.1. Toxicity	
12.1.1. Substances	
, .	PHENYLENEOXYMETHYLENE)]BISOXIRANE (CAS: 1675-54-3)
Fish toxicity :	LC50 = 1.3 mg/l
	Duration of exposure : 96 h
	OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)
Crustacean toxicity :	EC50 = 2.1 mg/l
	Species : Daphnia sp.
	Duration of exposure : 48 h
	OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)
	NOEC = $0.3 \text{ mg/l}$

Species : Rabbit

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

PB 250 - 765

NOEC = 0.3 mg/l Species : Daphnia magna Duration of exposure : 21 jours OCDE Ligne directrice 211 (Daphnia magna, essai de reproduction)

Version 14.1 (24-06-2022) - Page 9/12

Algae toxicity :

ECr50 > 11 mg/l Duration of exposure : 72 h

AFETY DATA SHEET (REGULATION (EC) n° 1 3 250 - 765	907/2006 - REACH)	Version 14.1 (24-06-2022) - Page 10/1
FORMALDEHYDE, OLIGOMERIC REACTION	ON PRODUCTS WITH 1-CHI ORO-2 3-FE	
Fish toxicity :	LC50 = 2.54 mg/l	
	Duration of exposure : 96 h	
Crustacean toxicity :	EC50 = 2.55 mg/l	
	Species : Daphnia sp.	
	Duration of exposure : 48 h	) aphnia sp., essai d'immobilisation immédiate)
Algae toxicity :	ECr50 > 1000 mg/l	
	Species : Selenastrum capric	ornutum
	Duration of exposure : 72 h	
	OCDE Ligne directrice 201 (A	lgues, Essai d'inhibition de la croissance)
12.1.2. Mixtures		
No aquatic toxicity data available for the mixt	ure.	
12.2. Persistence and degradability		
12.2.1. Substances		
2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHE	ENYLENEOXYMETHYLENE)]BISOXIRAN	E (CAS: 1675-54-3)
Biodegradability :	<b>o i</b>	ble, the substance is considered as not
	degrading quickly.	
FORMALDEHYDE, OLIGOMERIC REACTION	ON PRODUCTS WITH 1-CHLORO-2,3-EF	POXYPROPANE AND PHENOL
Biodegradability :	Non-rapidly degradable.	
12.3. Bioaccumulative potential		
12.3.1. Substances		
2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHE	ENYLENEOXYMETHYLENE)]BISOXIRAN	E (CAS: 1675-54-3)
Octanol/water partition coefficient :	log Koe <= 3.78	
Bioaccumulation :	BCF < 100.	
FORMALDEHYDE, OLIGOMERIC REACTION	ON PRODUCTS WITH 1-CHLORO-2,3-EF	POXYPROPANE AND PHENOL
Octanol/water partition coefficient :	log Koe = 3.3	
Bioaccumulation :	BCF = 150	
12.4. Mobility in soil		
No data available.		
12.5. Results of PBT and vPvB assessment		
No data available.		
12.6. Endocrine disrupting properties		
No data available.		
12.7. Other adverse effects		
No data available.	action of homorely for which a line of	(Annov L KPiwa)
German regulations concerning the classific	auon of nazards for water (WGK, AWS)	Annex I, NDWS):
WGK 2 : Hazardous for water.		
ECTION 13 : DISPOSAL CONSIDERATIO	INS	
Proper waste management of the mixture and		cordance with Directive 2008/98/EC
Topor waste management of the mixture an		

#### 13.1. Waste treatment methods

Do not pour into drains or waterways.

# Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

# Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

# Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

07 01 08 \* other still bottoms and reaction residues

#### **SECTION 14 : TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 - ICAO/IATA 2021).

# 14.1. UN number or ID number

3082

# 14.2. UN proper shipping name

UN3082=ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane)

#### 14.3. Transport hazard class(es)

- Classification :



9

# 14.4. Packing group

Ш

#### 14.5. Environmental hazards

- Environmentally hazardous material :



#### 14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel	
	9	M6	111	9	90	5 L	274 335	E1	3	-	
							375 601				
*Not s	subject to this	regulation if C	2 <= 5 I / 5 kg	(ADR 3.3.1 - I	DS 375)			-			
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage	Segregati		
								Handling	on		
	9	-	111	5 L	F-A. S-F	274 335	E1	Category	-		
						969		A			

#### \*Not subject to this regulation if Q <= 5 I / 5 kg (IMDG 3.3.1 - 2.10.2.7)

				(= = = =	- /				
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	9	-	III	964	450 L	964	450 L	A97 A158	E1
		0						A197 A215	n
	9	-	III	Y964	30 kg G	-	-	A97 A158	E1
								A197 A215	

\*Not subject to this regulation if Q <= 5 I / 5 kg (IATA 4.4.4 - DS A197)

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

Marine pollutant (IMDG 3.1.2.9):(formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)

# 14.7. Maritime transport in bulk according to IMO instruments

No data available.

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# Classification and labelling information included in section 2:

- The following regulations have been used:
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/643 (ATP 16)

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/849 (ATP 17)

Container information:

No data available.

Particular provisions :

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws) :

WGK 2 : Hazardous for water.

#### 15.2. Chemical safety assessment

No data available.

# **SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

# Wording of the phrases mentioned in section 3 :

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

#### Abbreviations and acronyms :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

EC50 : The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

NOEC : The concentration with no observed effect.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ATE : Acute Toxicity Estimate

BW : Body Weight

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

UFI : Unique formulation identifier.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

GHS07 : Exclamation mark

GHS09 : Environment

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.