

## Technical Data Sheet

---

**Product Code** VACleaseLT30Y1.5

**Product Description** Yellow, low temperature release film – 30 micron thickness  
Roll size 1.5 metres wide x 250 metres long  
Maximum usage temperature 150°C

---

**General Description** A highly flexible, non-perforated, polypropylene based release film. Suitable for use with epoxy prepreg up to 150°C and may be used in resin infusion applications.

---

### Properties

<b>Colour:</b>	Yellow
<b>Film Thickness:</b>	0.03mm (30 micron)
<b>Density:</b>	0.89-0.91 g/cm <sup>3</sup>
<b>Tensile Strength at Break:</b>	35 N/mm <sup>2</sup>
<b>Elongation at Break:</b>	500%
<b>Maximum Usage Temperature:</b>	150°C

### IMPORTANT INFORMATION:

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. Users must determine the product suitability for the end use application and assume all risks and liabilities.

Registered Office:  
VAC Innovation Ltd, Kilworth Lakes, Kilworth Road, North Kilworth, Leicestershire, LE17 6JG  
Registered in England No. 5340177

[www.vacinnovation.com](http://www.vacinnovation.com)  
Tel: 01858 882000

