

# PROFILE

Fact Sheet

## Profile UV Wax

High performance Carnauba-based wax



### Product Description

Profile UV Wax is a high performance, Carnauba-based wax incorporating special UV absorbers to give added protection to gelcoats and paints exposed to external weathering. The high Carnauba content ensures long lasting protection against rain and salt water whilst the UV absorbers protect against exposure to sunlight. Profile UV Wax will give a high gloss, long lasting finish on most surfaces and is particularly suitable for use on boats, caravans, trains and planes.

### Technical Information

Appearance: Thick yellow coloured liquid  
Viscosity: Low viscosity  
VOC Content: 18% of total product  
Relative Density: 1.0  
pH: 7  
Types of Surface: Polyester gelcoats, all types of painted and lacquered surfaces

### Product Information


Size	Code	Ctn Qty
1 litre (34 fl.oz.)	PROUVW-1000	6
5 litres (170 fl.oz.)	20105-5000	2

### Key Benefits

• Effective Results	Gives an excellent high gloss finishes to surfaces
• Lasting Protection	Highly durable UV Wax provides a strong barrier against water and UV degradation
• Tested Reliability	Laboratory tested according to BS EN ISO 4892, ASTM D5894 for extended weathering performance
• Simple to Use	Thick creamy liquid formula is easy to apply either by hand or by machine. It can also be used in damp weather and is resistant to drying out, even in sunny conditions

## Use With

### Hand Application



Farécla Finishing Cloth  
FC-3


### Machine Application



G Mop 8" Advanced Lambswool Pad  
AGM-LWP8




G Mop 8" Advanced Back Plate  
AGM-BP814 (14mm)




Farécla Finishing Cloth  
FC-3

## How To Use


### Hand Application



Shake the bottle and apply Profile UV Wax to the surface with a Finishing Cloth PROUVW-1000 (1 ltr)



Work 1m<sup>2</sup> sections, spread the wax in an overlapping action and ensure even coverage FC-3 (cloth)




Allow the wax to dry to a haze. Note: this will take a few seconds under normal conditions




Wipe surface with a Farécla Finishing Cloth FC-3 (cloth)

Repeat if necessary


### Machine Application



Shake the bottle and apply Profile UV Wax to the surface or machine PROUVW-1000 (1 ltr)



Attach Lambswool Pad, spread product and compound at 1200 - 1500rpm AGM-LWP8 (pad)



Wipe clean with a Farécla Finishing Cloth FC-3 (cloth)

\*It is always recommended to test on an inconspicuous area prior to general use

## Additional Information

Profile UV Wax is used on boats, RV's, trucks, trains and planes to give a high gloss, durable finish either during manufacture at final inspection or for regular cleaning and maintenance. It is particularly used to protect surfaces from UV degradation and weathering, giving an excellent deep gloss finish.