

Product : **PC4811000** Style : PW Customer Spec:

Description : 375GSM/PW/TR30 6K 1.2%A size/1000mm

| | | | |
|-------------------|-----------|--------------------|------------------|
| Warp Fibre | AF | Fibre | Ends/10cm |
| | AF062 | TR30S 6K 1.2% size | |
| | | | |
| | | | 47.3 ±2.0 |

| | | | |
|-------------------|-----------|--------------------|-------------------|
| Weft Fibre | AF | Fibre | Picks/10cm |
| | AF062 | TR30S 6K 1.2% size | |
| | | | |
| | | | 47.3 ±2.0 |

| | |
|------------------|-----------------------------|
| Leno Yarn | K29/220Dtex Twisted (AF175) |
|------------------|-----------------------------|

Tolerances/Testing/Frequency

Product Quality Plan C

| Check | Test Method | Nominal | Tolerance. |
|-------------------------|-------------|----------------|--------------|
| Mass | 001/2/8 | 375 | ±10 gsm |
| Width | 003 | 1000 | -0, +10mm |
| Ends/10cm | 004/005 | 47.3 | |
| Picks/10cm | 004/005 | 47.3 | ±2.0 |
| Picks/Inch | 010 | 12.01 | |
| Check | Test Method | Maximum | |
| Weft Bow | 006 | 30 mm/mt width | |
| Warp Bow | 007 | 5 mm/mt length | |
| Nominal Length (metres) | | 103 | |
| Construction | 012 | Verify | |
| Thickness | 011 | Verify | |

Test Methods details refer to information

| | |
|------------------------------|--|
| Special Instruction : | |
|------------------------------|--|

This document is un-controlled and is not subject to any up-dates which may undertake in the future