

PROFILE

Fact Sheet

Polymer Wax

High Performance Polymeric Wax



Product Description

Profile Polymer Wax is a high performance polymeric wax specially developed for ultimate gloss and water resistance. It is extremely fast and easy to use by hand or machine and is sufficiently liquid to be sprayed onto surfaces using either a small hand spray bottle or pump spray system. It is highly resistant to drying out and can be polished off easily to leave a durable high gloss on most surfaces.

Product Information

Size	Code	Ctn Qty
1 litre (34 fl.oz.)	PPW106	6
1 US gallon (3.785 ltrs)	PPW301	2

Technical Information


Appearance: Pink coloured liquid
Viscosity: Low / medium viscosity
VOC Content: 15% of total product
Relative Density: 0.99
pH: TBA
Types of Surface: Any painted or Industrial Surface

Key Benefits

• Fast	Quick and easy to use making short work of large surfaces such as on boats, caravans, trucks and planes
• Superb Finish	Delivers a high gloss finish of excellent evenness and clarity even on blacks and dark colours
• Protection	Highly water resistant providing a durable protective coating repelling many common contaminants
• Easy Application	Can be applied by hand or machine under most conditions and is resistant to drying
• Sprayable	Low viscosity sprayable formulation for ultra fast application

Use With

Hand Application




Farécla Finishing Cloth
FC-3

Spray Application



Water Spray Bottle
WSB




Farécla Finishing Cloth
FC-3


Machine Application



G Mop 8" Advanced
Lambswool Pad
AGM-LWP8




G Mop 8" Advanced
Back Plate
AGM-BP814 (14mm)




Farécla Finishing Cloth
FC-3

How To Use


Hand or Spray Application




Shake well before use
PPW106 (1 ltr)
PPW301 (1 US gallon)




Apply product to surface with
Finishing Cloth or spray
FC-3 (cloth)
WSB (bottle)



Using light pressure, apply to surface in an overlapping action to ensure even coverage




Allow wax to dry to a haze (note: this will only take a few seconds under most conditions)




Polish to a deep gloss shine (Note: 10-20 sq ft to be treated at a time)


Machine Application




Attach Lambswool Pad to polishing machine
AGM-LWP8 (Lambswool)



Shake well, apply a small amount of product and spread with pad to reduce throw off



Polish at a recommended speed of 1200 - 1500rpm



Wipe clean with Finishing Cloth
FC-3 (cloth)