

Technical Data Sheet

Product Code

VACtiteLTG

Product Description

Extra wide, green, vacuum bagging film
Available in Sheet width: 2m
Available in 'V' sheet widths: 2m (open 4m)
Available in gusset-folded sheet widths: 2m (open to either 6m; 8m; 12m or 16m)
Roll lengths vary from 400m to 70m (length reduces with width)
Maximum usage temperature 120°C

General Description

A wide, mono-layer, nylon blend bagging film for oven and autoclave processing.
Supplied as a gusset-folded sheet film.

Properties

| | |
|-----------------------------------|-------------------------------------|
| Colour: | Green |
| Film Thickness: | 0.075mm |
| Density: | 0.95g/cm ³ |
| Yield: | 15.1 m ² /Kg @ 70 micron |
| Tensile Strength At Break: | 38 Mpa |
| Tensile Strain At Break: | 500% |
| Maximum Usage Temperature: | 120°C |

IMPORTANT INFORMATION:

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. Users must determine the product suitability for the end use application and assume all risks and liabilities.

Registered Office:
VAC Innovation Ltd, Kilworth Lakes, Kilworth Road, North Kilworth, Leicestershire, LE17 6JG
Registered in England No. 5340177

www.vacinnovation.com
Tel: 01858 882000

