

Fabric Data Sheet

Product : **DV7941000** Style : 3x1TW Customer Spec:

Description : 228GSM/3x1TW/FT300 3K, Kevlar K49 1580 Dtex/1000mm

Warp Fibre	AF	Fibre	Ends/10cm 63 ±2.5
	AF996	FT300B 3000 40B	
	AF126	Kevlar 49-T-968 1580Dtex	

Weft Fibre	AF	Fibre	Picks/10cm 63 ±2.5
	AF996	FT300B 3000 40B	
	AF126	Kevlar 49-T-968 1580Dtex	

Leno Yarn	K29/220Dtex
------------------	-------------

Tolerances/Testing/Frequency

Product Quality Plan C

Check	Test Method	Nominal	Tolerance.
Mass	001/2/8	228	±4 gsm
Width	003	1000	-0, +10mm
Ends/10cm	004/005	63	
Picks/10cm	004/005	63	±2.5
Picks/Inch	010	16.00	
Check	Test Method	Maximum	
Weft Bow	006	30 mm/mt width	
Warp Bow	007	5 mm/mt length	
Nominal Length (metres)		50	
Construction	012	Verify	
Thickness	011	Verify	

Test Methods details refer to information as set in Sigmatex Quality Manual

Special Instruction :

This document is un-controlled and is not subject to any up-dates which may undertake in the future