

A8888

Release fabric

Ideally suited to medium temperature applications

Features

- Silicone coated nylon fabric.
- Coated with heat cured silicone release solution, to aid removal from the cured laminate.
- Some phenolic resins are known to adhere to nylon release fabrics, and it is therefore recommended that the customer conduct their own internal compatibility tests.
- When using release fabrics on composite laminates that will be subject to secondary bonding or painting operations, there is a potential for minor transfer onto the component, despite the release solution being fully polymerised. It is therefore recommended that prior to bonding or painting the laminate should be suitable prepared (industry standard method is preparation by slight abrading or sanding of the surface followed by cleaning with an approved solvent).

Properties

Maximum cure temperature	204°C	400°F
Colour	Green	
Fabric type	Nylon	
Fabric weight	75g/m ²	2.2oz/yd ²
Release coating	Silicone	

Availability

Standard width	1.52m	60in
Standard length	100m	109yd
	Slit widths available	

Storage

No special storage conditions required.

Health & safety

Handling of these products must conform to individual company guidelines and health and safety regulations.

All statements, technical information and recommendations contained in this data sheet are given in good faith and are based on tests believed to be reliable, but their accuracy and completeness are not guaranteed. They do not constitute an offer to any person and shall not be deemed to form the basis of any subsequent contract. All products are sold subject to the Cytec's Standard Terms and conditions of Sale. Accordingly, the user shall determine the suitability of the products for their intended use prior to purchase and shall assume all risk and liability in connection therewith. It is the responsibility of those wishing to sell items made from or embodying the products to inform the user of the properties of the products and the purposes for which they may be suitable, together with all precautionary measures required in handling those products. The information contained herein is under constant review and liable to be modified from time to time.

© Copyright 2012 – Cytec Process Materials (Keighley) Ltd, Cytec Process Materials (CA) Inc, Cytec Process Materials (Toulouse) Sarl, Cytec Process Materials (Milan) Srl. All rights reserved worldwide. All trademarks or registered trademarks are the property of their respective owners.