

Technical Data Sheet

Product Code

VACtiteSRG

Product Description

Self releasing multilayer nylon vacuum bagging film (gusset folded)
Widths available:-
86mm (3.5"), 100mm (4"), 125mm (5"), 150mm (6"), 200mm (8"), 250mm (10"),
300mm (12"), 400mm (16"), 450mm (18")
Roll length 200 metres

General Description

Self releasing vacuum bagging film specifically designed to provide easy removal from the inside of hollow composite structures after cure. The use of a self-releasing bag helps to avoid damage to the component. The film is ideal for use in both oven and autoclave cures up to 160°C. It is compatible with phenolic and epoxy prepregs.

Properties

Colour:	Green
Film Thickness:	70 μ \pm 10% - designation
Elongation:	MD 445% \pm 10% TD 350% \pm 10%
Tensile (break):	MD 50 N/mm ² \pm 10% TD 42 N/mm ² \pm 10%
Maximum Usage Temperature:	160°C

IMPORTANT INFORMATION:

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. Users must determine the product suitability for the end use application and assume all risks and liabilities.

Registered Office:
VAC Innovation Ltd, Kilworth Lakes, Kilworth Road, North Kilworth, Leicestershire, LE17 6JG
Registered in England No. 5340177

www.vacinnovation.com
Tel: 01858 882000

