

INDASA ORBITAL PALM SANDER

MARKETS



Automotive Marine & Comp



Wood



Other Markets

FORMS



Disc

FEATURES

Advanced composite materials

Ergonomic design

Fully compatible with INDASA's Abrasives System

Vacuum dust extraction

Variable speed regulator

BENEFITS

Optimum operator comfort

Improved sanding efficiency

Maximized performance

Cleaner working environment

Optimum working speed

APPLICATION SUGGESTIONS

Sanding



INDASA ORBITAL PALM SANDER

FASTENING SYSTEM / BACKING PAD



PRODUCT SPECIFICATIONS

| Pad size | Dust extract. system | Orbit (mm) | Free speed (RPM) | Air consump. (l/min)CFM | Working pressure (bar) | Weight (kg) | Vibration (m/sec ²) | Sound level (dBA) |
|----------|-----------------------|------------|------------------|-------------------------|------------------------|-------------|---------------------------------|-------------------|
| 75 mm | No vacuum | 2,5 | 12000 | 481-17 | 6,2 | 0,60 | 2,00 | 80 |
| 75 mm | Central vacuum | 2,5 | 12000 | 481-17 | 6,2 | 0,65 | 2,00 | 80 |
| 75 mm | Self generated vacuum | 2,5 | 12000 | 481-17 | 6,2 | 0,67 | 2,00 | 80 |
| 125 mm | No Vacuum | 2,5 | 12000 | 481-17 | 6,2 | 0,78 | 2,10 | 79 |
| 125 mm | Central vacuum | 2,5 | 12000 | 481-17 | 6,2 | 0,84 | 2,10 | 79 |
| 125 mm | Self generated vacuum | 2,5 | 12000 | 481-17 | 6,2 | 0,86 | 2,10 | 83 |
| 125 mm | No vacuum | 5 | 12000 | 481-17 | 6,2 | 0,81 | 2,60 | 80 |
| 125 mm | Central vacuum | 5 | 12000 | 481-17 | 6,2 | 0,87 | 2,60 | 79 |
| 125 mm | Self generated vacuum | 5 | 12000 | 481-17 | 6,2 | 0,89 | 6,50 | 85 |
| 150 mm | No vacuum | 2,5 | 12000 | 481-17 | 6,2 | 0,82 | 3,30 | 83 |
| 150 mm | Central vacuum | 2,5 | 12000 | 481-17 | 6,2 | 0,91 | 3,30 | 83 |
| 150 mm | Self generated vacuum | 2,5 | 12000 | 481-17 | 6,2 | 0,91 | 3,30 | 83 |
| 150 mm | No Vacuum | 5 | 12000 | 481-17 | 6,2 | 0,85 | 3,70 | 79 |
| 150 mm | Central vacuum | 5 | 12000 | 481-17 | 6,2 | 0,91 | 3,10 | 77 |
| 150 mm | Self generated vacuum | 5 | 12000 | 481-17 | 6,2 | 0,95 | 3,50 | 85 |