

Technical Data Sheet

Product Code	VACflexP
Product Description	Soft, pink, nylon bagging film (lay-flat tube) Roll length - 150m

General Description VACflexP is a pink, heat-stabilized, mono-layer nylon bagging film, providing the perfect solution for oven and autoclave processing of complex parts. It is a soft and strong vacuum bagging film, offering excellent puncture resistance.

Properties

Colour:	Pink	
Film Thickness:	0.050mm +/-10%	ISO 4593
Density	1.13g/cm ³	Internal
Tensile strength at break MD:	95 N/mm ² +/-10%	ASTM D882
Tensile strength at break TD:	90 N/mm ² +/-10%	ASTM D882
Elongation at break MD:	320% +/-10%	ASTM D882
Elongation at break TD:	370% +/-10%	ASTM D882
Maximum Usage Temperature:	204°C	

IMPORTANT INFORMATION:

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. Users must determine the product suitability for the end use application and assume all risks and liabilities.

Registered Office:
VAC Innovation Ltd, Wheatfield Way, Hinckley, Leicestershire, LE10 1YG
Registered in England No. 5340177

www.vacinnovation.com
Tel: 01858 882000

