

# PROFILE

Fact Sheet

# Profile 500

Light Cut Compound



## Product Information

| Size                  | Code        | Ctn Qty |
|-----------------------|-------------|---------|
| 220g                  | PRO500-0200 | 24      |
| 1 litre (34 fl.oz.)   | PRO500-1400 | 6       |
| 5 litres (170 fl.oz.) | 20501-5000  | 2       |

## Product Description

Profile 500 is a light cut, water-based compound used primarily as a second finishing step to remove swirl marks and give a high gloss finish. It will remove light scratching, restore colour and improve clarity and depth on dark colours.

## Technical Information

Appearance: White liquid  
Viscosity: Low - medium viscosity  
VOC Content: 14.165% of total product  
Relative Density: 1.16  
pH: 10  
Types of Surface: Polyester, acrylic and epoxy resins and gelcoats, industrial paint finishes, wood lacquers, solid surfaces

## Key Benefits

|                         |   |
|-------------------------|---|
| • Value                 | Economical in use due to its low viscosity  |
| • Effective and Precise | Fine abrasive formulation to remove marks without scratching  |
| • High Gloss Result     | Contains no added fillers, giving a permanent gloss finish with depth and clarity, even on dark colours, with no risk of die-back |
| • Safe Solutions        | Water based with low VOC content for safer working and easier clean-up  |

## Use With


### Primary Application



G Mop 8" Advanced  
Lambswool Pad  
AGM-LWP8



G Mop 8" Advanced  
Back Plate  
AGM-BP814




Farécla Finishing  
Cloth  
FC-3


### Secondary Application



G Mop 8" Advanced  
Polishing Foam  
AGM-PF8




G Mop 8" Advanced  
Back Plate  
AGM-BP814




Farécla Finishing  
Cloth  
FC-3

## How To Use

### Machine Application




Shake well and  
apply a small  
amount of  
compound to  
surface  
PRO500-1400 (ltr)



Attach Lambswool  
Pad, spread  
product and  
compound at  
1400 - 1600rpm  
AGM-LWP8 (pad)



Keep the polishing  
machine  
continuously  
moving and apply  
light pressure



Wipe clean with a  
Farécla Finishing  
Cloth  
FC-3 (cloth)

\*It is always recommended to test on an inconspicuous area prior to general use

## Additional Information

Profile 500 can be used as a finishing step to increase gloss and reduce swirl on all types of gelcoats and paints for production of composite parts in marine, transport and sanitary ware applications. It can be used on most paints and wood finishes, giving excellent clarity on dark colours and helping to remove any residual abrasive cutting marks.