

TYPE APPROVAL CERTIFICATE

Certificate No: **TAK00000C6** Revision No: 2

Head of Section

			4		400	
h	10	10	to	60	rtif	\ ''
	13	13	LU	CE		v .

That the Glass Fibre Products

with type designation(s)

Uni-axial; 0° (150-2400 g/m²) and 90° (150-1200 g/m²) with or without CSM (50-600 g/m²)

Issued to

Vitrulan Composites Oy, Mikkeli Plant Mikkeli, Finland

is found to comply with

Application:

DNV GL class programme DNVGL-CP-0467 – Type approval – Uni- and multi-axial multi-ply fabrics made of glass fibres

DNV GL rules for classification - High speed and light craft

DNV GL standard DNVGL-ST-0342 - Craft

Det Norske Veritas' Standards for Certification No. 2.20, Lifeboats and Rescue Boats, 2007

Manufacturing of FRP laminates.	
Product(s) approved by this certificate is/are accepted for	installation on all vessels classed by DNV.
Issued at Høvik on 2021-08-19	
This Certificate is valid until 2026-08-18.	for DNV
DNV local station: Helsinki FIS	
Approval Engineer: Gisle Hersvik	
	Gustav Heiberg

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: TA 251 Revision: 2021-03 www.dnv.com Page 1 of 2

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-006899-5** Certificate No: **TAK00000C6**

Revision No: 2

Product description

Uni-axial Glass Fibre products, of 0° and 90° orientation:

- 0° (150-2400 g/m²) with or without CSM (50-600 g/m²)
- 90° (150-1200 g/m²) with or without CSM (50-600 g/m²).

Legends:

Uni-axial: 0° (longitudinal) or 90° (transverse)

CSM: Chopped Strand Mat

Application/Limitation

The approval covers the weight ranges listed above.

Any significant changes in design and / or quality of the material will render the approval invalid.

Type Approval documentation

Tests carried out

Type Testing carried out according to Type Approval documentation.

Marking of product

Product shall be marked with *manufacturer's name*: **Vitrulan Composites Oy, Mikkeli Plant, Finland** and *type designation*.

The marking is to be carried out in such a way that it is visible, legible and indelible. The marking of product is to enable traceability to the DNV Type Approval Certificate.

Periodical assessment

The scope of the Periodical Assessment is to verify that the conditions stipulated for the Type Approval is complied with and that no alterations are made to the product design or choice of materials.

Periodical assessments (for Certificate Retention and Certificate Renewal) shall be performed according to DNVGL-CP-0338.

This certificate is only valid if required Periodical assessments are carried out with satisfactory results. To check the validity of this certificate, please look it up in https://approvalfinder.dnvgl.com

END OF CERTIFICATE

Form code: TA 251 Revision: 2021-03 www.dnv.com Page 2 of 2